

REFERENCES

REFERENCES

- [1] Khedari, J., Sangprajak, A. and Hirunlabh, J. (2001). Thailand climatic zones. **Journal of Renewable Energy**, 25, 267-280.
- [2] The development of renewable energy and energy conservation. (July 14, 2006). **Solar Technology**. Retrieved February 14, 2014, from http://www.stasolar.org/SUNTECH/sun_tech.htm
- [3] Kunchornrat, A., Namprakai, P. and Du Pont, P.T. (2009). The impacts of climate zones on the energy performance of existing Thai building. **Resources, Conservation and Recycling**, 53(10), 545-551.
- [4] Al-Awadhi, E.M. (2008). Thermal analysis of a building brick containing phase change material. **Energy and Buildings**, 40, 351-357.
- [5] Castell, A., Martorell, I., Perez, G. and Cabeza, L.F. (2010). Experimental study of using PCM in brick constructive solutions for passive cooling. **Energy and Buildings**, 42, 534-540.
- [6] Royon, L., Bontemps, A. (July, 2011). Developing new phase change material components to improve energy savings and comfort in building technologies. Retrieved March 10, 2014, from <http://yadda.icm.edu.pl/yadda/element/bwmeta1.element.elsevier-1efc683a-4c2a-34df-9ce7-ec6c6d809063>
- [7] Sharma, A., Tyagi, V.V., Chen, C.R. and Buddhi, D. (2009). Review on thermal energy storage with phase change materials and applications. **Renewable and Sustainable Energy Reviews**, 13, 318-345.
- [8] Swet, J. (1980). Phase changes storage in passive solar architecture. In **Proceedings of the 5th National Passive Solar Conference** (pp. 282-286). Amhearst: Massachusetts.
- [9] Ghoneim, A.A., Klein, S.A. and Duffie, J.A. (1991). Analysis of collector-storage building walls using phase change materials. **Solar Energy**, 47(1), 237-242.
- [10] Schossig, P., Henning H.M., Gschwander, S. and Haussmann, T. (2005). Micro-encapsulated phase change materials integrated into construction materials. **Solar Energy Mater Solar Cells**, 89, 297-306.

- [11] Kisssock, J.K., Hamming, J.M., Whitney, T.I., Drake, M.L. (1998). **Testing and simulation of phase change wallboard for thermal storage in buildings.** New York: n.p.
- [12] Kalousck, M. and Hirs, J. (2002). Simulation of the summer indoor thermal comfort by using wallboard with phase change material, **Eurosun, Bologna, N.P.:** n.p.
- [13] Mehling, H. (April 18, 2004). Strategic project “Innovative PCM-technology” - results and future perspectives. In **8th Expert Meeting and Work Shop.** Turkey: Kizkalesi.
- [14] Frank, B. (2002). **Phase change material for space heating and cooling, Sustainable Energy Center.** Australia: University of South Australia.
- [15] Benard, C., Gobin, D. and Gutierrez, M. (1981). Experimental results of a latent heat solar roof used for breeding chickens. **Solar Energy**, 6(4), 347–354.
- [16] Chou, H.M., Chen, C.R. and Nguyen, V.L. (2013). A new design of metal-sheet cool roof using PCM. **Energy and Buildings**, 57, 42–50.
- [17] Ong, K.S. (2011). Temperature reduction in attic and ceiling via insulation of several passive roof designs. **Energy Conversion and Management**, 52, 2405–2411.
- [18] Alawadhi, M.E. and Alqallaf, H.J. (2011). Building roof with conical holes containing PCM to reduce the cooling load: Numerical study. **Energy Conversion and Management**, 52, 2958–2964.
- [19] Tao, H.S. (2004). **Research for developing aerated concrete by using fly ash with high calcium of Gehua power plant in Hongshan.** Doctoral dissertation, Ph.D., Wuhan University of Technology, WuHan.
- [20] Alduaij, J., Alshaleh, K., Haque, M.N. and Ellaithy, K. (1999). Lightweight concrete in hot coastal areas. **Cement and Concrete Composites**, 21, 453-458.
- [21] Cabrillac, R., Florio, B., Beaucour, A.L., Dumontet, H. and Ortola, S. (2006). Experimental study of the mechanical anisotropy of aerated concretes and of the adjustment parameters of the introduced porosity. **Construction and Building Materials**, 20, 286–295.

- [22] Kearsley, E.P. and Wainwright, P.J. (2001). Porosity and permeability of foamed concrete. **Cement and Concrete Research**, 31(5), 805–812.
- [23] Koronthalyova, O. (2011). Moisture storage capacity and microstructure of ceramic brick and autoclaved aerated concrete. **Construction and Building Materials**, 25, 879-885.
- [24] Kurama, H., Topcu, I.B. and Karakurt, C. (2009). Properties of the autoclaved aerated concrete produced from coal bottom ash. **Journal of Materials Processing Technology**, 209, 767-773.
- [25] Topcu, I.B. and Isikdag, B. (2008). Effect of expanded perlite aggregate on the properties of lightweight concrete. **Journal of Materials Processing Technology**, 204, 34-38.
- [26] Huang, X.Y., Ni, W., Cui, W.H., Wang, Z.J. and Zhu, L.P. (2012). Preparation of autoclaved aerated concrete using copper tailings and blast furnace slag. **Construction and Building Materials**, 27, 1-5.
- [27] Mostafa, N.Y. (2005). Influence of air-cooled slag on physicochemical properties of autoclaved aerated concrete. **Cement and Concrete Research**, 35, 1349-1357.
- [28] Ma, B.G. and Zheng, X. (1999). Study on a new kind of aerated concrete containing efflorescence sand-phosphorus slag-lime. **Journal of Building Materials**, 2(3), 223-228.
- [29] Li, F.X., Chen, Y.Z. and Long, S.Z. (2008). Experimental investigation on aerated concrete with addition of lead–zinc tailings. **Journal of Southwest Jiaotong University**, 43(6), 810-815.
- [30] Wang, Y., Yin, J., Chen, J.C. and Peng, C.Q. (2000). Aerocrete made with low silicon tailings of Cheng Chao iron ore mine. **Journal Wuhan University of Technology, Materials Science Edition**, 15(2), 58-62.
- [31] Jitchaiyaphum, K., Sinsiri, T., Jaturapitakkul, C. and Chindaprasirt, P. (2013). Cellular lightweight concrete containing high-calcium fly ash and natural zeolite. **International Journal of Minerals, Metallurgy and Materials**, 20(5), 462-471.

- [32] Wang, Q.K., Chen, Y.Z., Li, F.X., Sun, T. and Xu, B.B. (2006). Microstructure and properties of silty siliceous crushed stone-lime aerated concrete. **Journal of Wuhan University of Technology, Materials Science Edition**, 21(2), 17-20.
- [33] Na Ayuthaya, B.I., Jantawong, P. and Ungkoon, Y. (2010). Study of hygrothermal performance of autoclaved aerated concrete mixed with sugar sediment and autoclaved aerated concrete walls under climate of Bangkok. **Ladkrabang Engineering Journal**, 27(4), 19-24.
- [34] Ungkoon, Y. (2011). Influence of Sugar Sediment Mixture on Mechanical Property of Autoclaved Aerated Concrete Elements. **Ladkrabang Engineering Journal**, 28(3), 55-60.
- [35] Hebel. (November 4, 2010). **The History of AAC at the Wayback Machine**. Retrieved March 24, 2014, from <https://web.archive.org/web/20101104001651/http://www.hebel.co.nz/about/hebel%20history.php>
- [36] Swedish Association of Historical Buildings. (April 4, 2004). **Pioneering work in the early days of concrete - history 1890–1950**. Retrieved March 24, 2014, from <http://www.byggnadsvard.se/material/pionj%C3%A4rnsatser-i-betongens-barndom-konstruktionsbetongens-historia-1890-1950>
- [37] Aroni, S., Groot, G.J.D., Robinson M.J., Svanholm, G. and Wittman, F.H. (1993). **Autoclaved Aerated Concrete - properties, testing and design (Rilem Recommended Practice)**. London: E & FN Spon Publications.
- [38] Thai Industrial Standards Institute. (1998). **Aerated concrete reinforce lightweight panels TIS.1505-1998**. Bangkok: Ministry of Industry
- [39] Merlino, S., Bonaccorsi, E. and Kampf, A.R. (2000). Tobermorite 14A°: crystal structure and OD character. In D. Rammlmair, J. Mederer, T. Oberthur, R.B. Heimann, H. Pentinghaus (Eds.), **Applied Mineralogy** (pp. 859–861). Balkema: Rotterdam.
- [40] Ungkoon, Y., Shin, U.C., Hirunlabh, J., Yodovard, P. and Khedari, J. (May 2-4, 2005). **Thermal Inertia Properties of Autoclaved Aerated Concrete**. Chonburi: King Mongkut's University of Technology Thonburi.
- [41] Zheng, Q. and Wang, W. (2000). Calcium silicate based high efficiency thermal insulation. **British Ceramic Transactions**, 99(4), 187-190.

- [42] Narayanan, N. and Ramamurthy, K. (2000). Microstructural investigations on aerated concrete. **Cement and Concrete Research**, 30, 457-464.
- [43] Regin, A.F., Solanki, S.C. and Saini, J.S. (2008). Heat transfer characteristics of thermal energy storage system using PCM capsules: a review. **Renewable & Sustainable Energy Reviews**, 12, 2438-2458.
- [44] Abhat, A. (1983). Low temperature latent heat thermal energy storage: heat storage materials. **Solar Energy**, 30, 313-332.
- [45] Tae, S. and Shin, S. (2009). Current work and future trends for sustainable buildings in South Korea. **Renewable & Sustainable Energy Reviews**, 13, 1910-1921.
- [46] Jeon, J., Lee, J.H., Seo, J., Jeong, S.G. and Kim, S. (2013). Application of PCM thermal energy storage system to reduce building energy consumption. **Journal of Thermal Analysis and Calorimetry**, 111, 279-288.
- [47] Tyagi, V.V. and Buddhi, D. (2007). PCM thermal storage in buildings: a state of art. **Renewable & Sustainable Energy Reviews**, 11, 1146-1166.
- [48] Khudhair, A.M. and Farid, M.M. (2004). A review on energy conservation in building applications with thermal storage by latent heat using phase change materials. **Energy Conversion and Management**, 45, 263-275.
- [49] Kim, S. and Drzal, L.T. (2009). High latent heat storage and high thermal conductive phase change materials using exfoliated graphite nanoplatelets. **Solar Energy Materials and Solar Cells**, 93, 136-142.
- [50] Hong, K. and Park, S. (1999). Melamine resin microcapsules containing fragrant oil: synthesis and characterization. **Materials Chemistry and Physics**, 58, 128-131.
- [51] Nelson, G. (2002). Application of microencapsulation in textiles. **International Journal of Pharmaceutics**, 242, 55-62.
- [52] Zhang, X.X., Fan, Y.F., Tao, X.M. and Yick, K.L. (2004). Fabrication and properties of microcapsules and nanocapsules containing n-octadecane. **Materials Chemistry and Physics**, 88, 300-307.
- [53] Lan, X., Tan, Z., Zou, G., Sun, L. and Zhang, T. (2004). Microencapsulation of n-eicosane as energy storage material. **Chinese Journal of Chemistry**, 22, 411-414.

- [54] Li, W., Zhang, X., Wang, X. and Niu, J. (2007). Preparation and characterization of microencapsulated phase change material with low remnant formaldehyde content. **Materials Chemistry and Physics**, 106, 437–442.
- [55] Wang, X., Niu, J. and Van Paassen, A.H.C. (2008). Raising evaporative cooling potentials using combined cooled ceiling and MPCM slurry storage. **Energy and Buildings**, 40, 1691–1698.
- [56] Diaconu, B.M. (2009). Transient thermal response of a PCM heat storage system. **Energy and Buildings**, 41, 212–219.
- [57] Lai, C., Chen, R.H. and Lin, C. (2010). Heat transfer and thermal storage behavior of gypsum boards incorporating micro-encapsulated PCM. **Energy and Buildings**, 42, 1259–1266.
- [58] Veerappan, M., Kalaiselvam, S., Iniyan, S. and Goic, R. (2009). Phase change characteristic study of spherical PCMs in solar energy storage. **Solar Energy**, 83, 1245–1252.
- [59] Bayes-Garcia, L., Ventola, L., Cordobilla, R., Benages, R., Calvet, T. and Cuevas-Diarte, M.A. (2010). Phase change materials (PCM) microcapsules with different shell compositions: Preparation, characterization and thermal stability. **Solar Energy Materials and Solar Cells**, 94, 1235–1240.
- [60] Hawlader, M.N.A., Uddin, M.S. and Khin, M.M. (2003). Microencapsulated PCM thermal energy storage system. **Applied Energy**, 74, 195–202.
- [61] Zou, G.L., Tan, Z.C., Lan, X.Z., Sun, L.X. and Zhang, T. (2004). Preparation and characterization of microencapsulated hexadecane used for thermal energy storage. **Chinese Chemical Letters**, 15, 729–732.
- [62] Liang, C., Lingling, X., Hongbo, S. and Zhibin, Z. (2009). Microencapsulation of butyl stearate as a phase change material by interfacial poly condensation in a poly urea system. **Energy Conversion and Management**, 50, 723–729.
- [63] Kim, E.Y. and Kim, H.D. (2005). Preparation and properties of microencapsulated octadecane with waterborne polyurethane. **Journal of Applied Polymer Science**, 96, 1596–1604.

- [64] Shin, Y., Yoo, D. and Son, K. (2005). Development of thermo regulating textile materials with microencapsulated phase change materials (PCM). IV. Performance properties and hand of fabrics treated with PCM microcapsules. **Journal of Applied Polymer Science**, 97, 910–915.
- [65] Su, J., Wang, L. and Ren, L. (2005). Preparation and characterization of double-MF shell micro PCMs used in building materials. **Journal of Applied Polymer Science**, 97, 1755–1762.
- [66] Zhang, X.X., Fan, Y.F., Tao, X.M. and Yick, K.L. (2005). Crystallization and prevention of super cooling of microencapsulated n-alkanes. **Journal of Colloid and Interface Science**, 281, 299–306.
- [67] Zhang, P., Hu, Y., Song, L., Ni, J., Xing, W. and Wang, J. (2010). Effect of expanded graphite on properties of high-density polyethylene/paraffin composite with intumescent flame retardant as a shape stabilized phase change material. **Solar Energy Materials and Solar Cells**, 94, 360–365.
- [68] Xu, X., Zhang, Y., Lin, K., Di, H. and Yang, R. (2005). Modeling and simulation on the thermal performance of shape-stabilized phase change material floor used in passive solar buildings. **Energy and Buildings**, 37, 1084–1091.
- [69] Lin, K., Zhang, Y., Xu, X., Di, H., Yang, R. and Qin, P. (2005). Experimental study of underfloor electric heating system with shape-stabilized PCM plates. **Energy and Buildings**, 37, 215–220.
- [70] Cheng, W., Zhang, R., Xie, K., Liu, N. and Wang, J. (2010). Heat conduction enhanced shape-stabilized paraffin/HDPE composite PCMs by graphite addition: preparation and thermal properties. **Solar Energy Materials and Solar Cells**, 94, 1636–1642.
- [71] Bayazitoglu, Y. and Ozisik, M.N. (1988). **Elements of Heat Transfer**. Singapore: McGraw-Hill.
- [72] Jin, X., Zhang, X.S., Cao, Y. and Wang, G. (2012). Thermal performance evaluation of the wall using heat flux time lag and decrement factor. **Energy and Buildings**, 47, 369–374.
- [73] Asan, H. and Sancaktar, Y.S. (1998). Effects of wall's thermophysical properties on time lag and decrement factor. **Energy and Buildings**, 28, 159–166.

- [74] US Environmental Protection Agency. (October 17, 2010). **Defining Life Cycle Assessment (LCA)**. Retrieved March 24, 2014, from <http://www.gdrc.org/uem/lca/lca-define.html>
- [75] Ecometrica. (April 25, 2013). **GHG Product Life Cycle Assessments**. Retrieved March 24, 2014, from <http://ecometrica.com/services/#lca>
- [76] International Organisation for Standardisation (ISO). (July 17, 2010). **ISO 14040 (2006): Environmental management – Life cycle assessment – Principles and framework**. Retrieved March 24, 2014, from http://www.iso.org/iso/catalogue_detail?csnumber=37456
- [77] International Organisation for Standardisation (ISO). (July 17, 2010). **ISO 14044 (2006): Environmental management – Life cycle assessment – Requirements and guidelines**. Retrieved March 24, 2014, from http://www.iso.org/iso/catalogue_detail?csnumber=38498
- [78] Rebitzer, G., Ekvall, T., Frischknecht, R., Hunkeler, D., Norris, G., et al. (2004). Life cycle assessment Part 1: Framework, goal and scope definition, inventory analysis, and applications. **Environment International**, 30, 701-720.
- [79] Ecomii. (October 19, 2010). **Cradle-to-cradle definition**. Retrieved March 24, 2014, from <http://www.ecomii.com/ecopedia/cradle-to-cradle>
- [80] Jiménez-González, C., Kim, S., Overcash, M. (2000). Methodology for developing gate-to-gate Life cycle inventory information. **The International Journal of Life Cycle Assessment**, 5, 153–159.
- [81] Loykhajon, S. (2011). **Technical comparison of the heat transfer of commercial materials**. Phitsanulok: Naresuan University.
- [82] Jaemjarad, O. (2011). **Investigation of the attic effect on thermal transmission**. Phitsanulok: Naresuan University.
- [83] Boonsuwan, A. (2006). **Study of the distribution and thermal lag heatin of multi-layered light weight concrete wall on different thickness**. Phitsanulok: Naresuan University.
- [84] Blank, L.T. and Tarquin, A.J. (1998). **Engineering Economy** (4th ed.). London: McGraw-Hill.

- [85] Yang, R.C., Zhu, J.P., Wu, Z.S., Wu, Z.R., Li, M. and Peng, C.H. (2011). Thermal insulation and strength of autoclaved light concrete. **Journal of Wuhan University of Technology Materials Science Edition**, 26(1), 132-136.
- [86] Narayanan, N. and Ramamurthy, K. (2000). Structure and properties of aerated concrete cement: a review. **Cement and Concrete Composites**, 22, 321-329.
- [87] Kus, H. and Carlsson, T. (2003). Microstructural investigations of naturally and artificially weathered autoclaved aerated concrete. **Cement and Concrete Research**, 33, 1423-1432.
- [88] Ungkoon, Y., Sittipunt, C., Namprakai, P., Jetipattaranat, W., Kim, K.S. and Charinpanitkul, T. (2007). Analysis of microstructure and properties of autoclaved aerated concrete wall construction materials. **Journal of Industrial and Engineering Chemistry**, 13(7), 1103-1108.
- [89] Thongtha, A., Angsukased, K. and Bongkarn, T. (2010). Fabrication of $(\text{Ba}_{1-x}\text{Sr}_x)(\text{Zr}_x\text{Ti}_{1-x})\text{O}_3$ ceramics prepared using the combustion technique. **Smart Materials and Structures**, 19, 124001.
- [90] Ng, S.C., Low, K.S. and Tioh, N.H. (2011). Newspaper sandwiched aerated lightweight concrete wall panels-Thermal inertia, transient thermal behavior and surface temperature prediction. **Energy and Buildings**, 43, 1636-1645.
- [91] Asan, H. (1998). Effects of Wall's insulation thickness and position on time lag and decrement factor. **Energy Buildings**, 28, 299-305.
- [92] Vijayalaxmi, J. (2010). Concept of overall thermal transfer value (OTTV) in design of building envelope to achieve energy efficiency. **International Journal of Thermal & Environmental Engineering**, 1(2), 75-80.
- [93] Chirarattananon, S. (November 19, 1992). Building energy efficiency in Thailand. In **Proceedings of the Symposium on Energy Efficient Buildings**, The University of Hong Kong: Hong Kong,
- [94] Provincial Electricity Authority. (February 3, 2014). **Rate of electricity consumption for the residency**. Retrieved December 5, 2013, from <http://www.pea.co.th/en/SitePages/home.aspx>

- [95] Environmental Protection Agency. (June 4, 1997). **Emission factor documentation for AP-42, Section 9.10.1.1, Sugarcane processing, Final report**. Retrieved March 24, 2014, from <http://www.epa.gov/ttnchie1/ap42/ch09/bgdocs/b9s10-1a.pdf>
- [96] Goedkoop M. and Spriensma R. (June 22, 2001). **The eco-indicator99: A damage oriented method for life cycle impact assessment**. Retrieved March 24, 2014, from http://www.pre-sustainability.com/download/misc/EI99_annexe_v3.pdf
- [97] Contreras, A.M., Rosa, E., Pe´rez, M., Langenhove, H.V. and Dewulf, J. (2009). Comparative life cycle assessment of four alternatives for using by-products of cane sugar production. **Journal of Cleaner Production**, 17, 772-779.

BIOGRAPHY

BIOGRAPHY

Name –Surname Atthakorn Thongtha
Date of Birth June 4, 1986
Address 19/1, Moo 5, Tom District, Muang, Phayao, 56000,
Thailand

Education Background

2011 M. Sc. (Applied Physics), Naresuan University,
Thailand
2009 B.Sc. (Physics), Naresuan University, Thailand

Publication

- Chaimongkon, U., Thongtha, A., and Bongkarn, T. The effects of firing temperatures and barium content on phase formation, microstructure and dielectric properties of lead barium titanate ceramics prepared via the combustion technique. **Current Applied Physics**, 11, S70-S76.
- Maneewan, S., Punin, W., Punlek C., Thongtha, A. and Kiatsiriroa, T. Feasibility of refuse derived fuel 5 composed of mechanical biological waste treatment and crude oil sludge. **Applied Mechanics and Materials**, 448-453, 699-708.
- Maneewan, S., Thongtha, A. and Punlek C. Coefficient of performance of thermoelectric cooling on nanofluids. **Applied Mechanics and Materials**, 459, 91-99.
- Thongtha, A., Angsukased, K. and Bongkarn, T. (2008). Effects of calcination temperatures on phase and morphology evolution of $(\text{Ba}_{0.25}\text{Sr}_{0.75})(\text{Zr}_{0.75}\text{Ti}_{0.25})\text{O}_3$ powders synthesized via solid-state reaction and combustion technique. **Advanced Materials Research**, 55, 197-200.

- Thongtha, A., Angsukased, K. and Bongkarn, T. (2010). Influences of firing temperatures on phase and morphology evolution of $(\text{Ba}_{0.25}\text{Sr}_{0.75})(\text{Zr}_{0.75}\text{Ti}_{0.25})\text{O}_3$ ceramics synthesized via solid-state reaction method. **Key Engineering Materials**, 421, 247-250.
- Thongtha, A., Angsukased, K. and Bongkarn, T. (2010). Fabrication of $(\text{Ba}_{1-x}\text{Sr}_x)(\text{Ti}_{1-x}\text{Zr}_x)\text{O}_3$ ceramics prepared using the combustion technique. **Smart Materials and Structures**, 19, 124001.
- Thongtha, A., Angsukased, K. and Bongkarn, T. (2010). Preparation of $(\text{Ba}_{1-x}\text{Sr}_x)(\text{Zr}_x\text{Ti}_{1-x})\text{O}_3$ ceramics via the solid state reaction method. **Ferroelectrics**, 403, 68-75.
- Thongtha, A. and Bongkarn, T. (2010). Fabrication and characterization of perovskite SrZrO_3 ceramics through a combustion technique. **Key Engineering Materials**, 421, 223-226.
- Thongtha, A. and Bongkarn, T. (2010). Effect of firing temperatures on phase and morphology evolution of CaZrO_3 ceramics synthesized using the combustion technique. **Ferroelectrics**, 403, 3-10.
- Thongtha, A. and Bongkarn, T. (2011). Fabrication and characterization of $0.904\text{Bi}_{0.5}\text{Na}_{0.5}\text{TiO}_3\text{-}0.040\text{Bi}_{0.5}\text{K}_{0.5}\text{TiO}_3\text{-}0.056\text{BaTiO}_3$ lead-free ceramics using the combustion technique. **Nu Science Journal**, 7(2), 10-19.
- Thongtha, A. and Bongkarn T. (2010). Fabrication and characterization of perovskite SrZrO_3 ceramics through a combustion technique. **Key Engineering Materials**, 421-422, 223-226.
- Thongtha, A. and Bongkarn, T. (2011). Optimum sintering temperature for fabrication of $0.8\text{Bi}_{0.5}\text{Na}_{0.5}\text{TiO}_3\text{-}0.2\text{Bi}_{0.5}\text{K}_{0.5}\text{TiO}_3$ lead-free ceramics by combustion technique. **Key Engineering Materials**, 474-476, 1754-1759.
- Thongtha, A. and Bongkarn, T. (2009). Phase formation and microstructure of barium zirconate ceramics prepared using the combustion technique. **Ferroelectrics**, 383, 33-39.

- Thongtha, A., Laowanidwatana, L. and Bongkarn, T. (2013). Phase formation, microstructure and dielectric properties of bismuth potassium titanate ceramic fabricated using the combustion technique. **Integrated Ferroelectrics**, 149(1), 32-38.
- Thongtha, A., Maneechukate, T., Laowanidwatana, L. and Bongkarn, T. (2013). Phase evolution, microstructure and dielectric properties of $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ ceramics fabricated by combustion technique. **Ferroelectrics**, 457, 23-29
- Thongtha, A., Maneewan, S., Punlek, C. and Ungkoon, Y. (2014). Application using sugar sediment to enhance mechanical properties of autoclaved aerated concrete. **Applied Mechanics and Materials**, 459, 664-668.
- Thongtha, A., Maneewan, S., Punlek, C. and Ungkoon, Y. (2013). Improving mechanical properties of autoclaved aerated concrete by sugar sediment. **Advance Materials Research**, 807-809, 1266-1269.
- Thongtha, A., Maneewan, S., Punlek, C. and Ungkoon, Y. (2013). Reducing heat Conduction of autoclaved aerated concrete wall using phase change material. **Advance Materials Research**, 807-809, 2779-2783.
- Thongtha, A., Tupmongkol, S. and Bongkarn, T. (2013). Combustion synthesis and characterization of perovskite $(\text{Pb}_{0.75}\text{Ca}_{0.13}\text{Sm}_{0.08})(\text{Ti}_{0.98}\text{Mn}_{0.02})\text{O}_3$ ceramics. **Ferroelectrics**, 455, 6-14.
- Thongtha, A., Wattanawikkam, C. and Bongkarn, T. (2011). Phase formation and dielectric properties of $(\text{Pb}_{0.925}\text{Ba}_{0.075})(\text{Zr}_{1-x}\text{Ti}_x)\text{O}_3$ ceramics prepared by the solid state reaction method. **Phase Transitions**, 84, 952-959.