

LIST OF CONTENTS

Chapter	Pages
I INTRODUCTION	1
Rationale for the study	1
Statement of the problem	4
Purpose of the study	5
Significance of the study	5
Scope of the study	7
Benefit of the study	8
II REVIEW OF RELATED LITERATURE AND RESEARCH	10
Review of Related Literature	10
Heat transfer	13
Electromagnetic spectrum	18
Atmospheric and solar radiation	20
Brewster's angle	21
IR-reflective pigments	23
III RESEARCH METHODOLOGY	26
Formulating the high solar reflective coating that optimize energy saving	26
The heat performance testing of small building was coated with the high solar reflective paint (Beger Cool UV Shield).....	30
Step of experiment	35
Energy saving of small building calculation.....	35
Determination of a conductivity and OTTV value	37
Achievements.....	39
The Numerical calculation for coated with high solar reflective paint for surface temperature through a wall	39

LIST OF CONTENTS (CONT.)

Chapter	Pages
IV RESULTS AND DISCUSSION	45
The result of different solar reflective value according to 6 different chemical parameters of paint formulation for both primer and top coat	45
The result of heat gain reduction, the energy consumption and energy saving from three small buildings	49
V CONCLUSION AND RECOMMENDATION	66
Conclusion	66
Recommendation	67
REFERENCES	68
APPENDIX	72
BIOGRAPHY	96

LIST OF TABLES

Table	Page
1 Parameter to be collected for energy balance.....	41
2 for primer - color: white, black, aluminum or metallic effect	45
3 for primer - dosage of microsphere ceramic: high and low dosage	46
4 for topcoat - dosage of IR pigment and normal pigment	46
5 for topcoat - dosage of insulate microsphere ceramic	46
6 for primer - contamination such as carbon black	47
7 for topcoat - opacity: low and high hiding power	47
8 The chemical ingredient of the Beger Cool UV Shield.....	48
9 Heat Gain comparison of 3 buildings.....	60
10 Average Energy Consumption comparison of 3 buildings.....	61
11 Average Electrical cost comparison of 3 buildings.....	62

LIST OF TABLES

Table	Page
1 Parameter to be collected for energy balance.....	41
2 for primer - color: white, black, aluminum or metallic effect.....	45
3 for primer - dosage of microsphere ceramic: high and low dosage	46
4 for topcoat - dosage of IR pigment and normal pigment	46
5 for topcoat - dosage of insulate microsphere ceramic.....	46
6 for primer - contamination such as carbon black	47
7 for topcoat - opacity: low and high hiding power	47
8 The chemical ingredient of the Beger Cool UV Shield.....	48
9 Heat Gain comparison of 3 buildings.....	60
10 Average Energy Consumption comparison of 3 buildings.....	61
11 Average Electrical cost comparison of 3 buildings.....	62

LIST OF FIGURES

Figures	Pages
1 Urban heat island (UHI) profile	1
2 Generation of urban heat island (UHI).....	3
3 The transfer of thermal energy occurs only through conduction, convection, radiation or any combination of these.....	14
4 The heat transfer – one dimension plane wall.....	15
5 The convection a) Forced convection b) Natural convection c) Boiling d) Condensation.....	16
6 The total heat energy on the material	17
7 Electromagnetic spectrum	19
8 Spectrum of magnetic waves, showing the heat ranges from radiation	19
9 Air molecules scatter blue light much more than they do red light.....	20
10 Graph of the Fresnel Equations showing the percent of incident light reflected for parallel and perpendicular polarizations.....	21
11 The Brewster's angle	22
12 Arctic reflective pigments	24
13 Spectrophotometer.....	28
14 Shimadzu UV 3100	28
15 Solar Reflective simulation programs (Cool Sim)	29
16 Emissometer	29
17 Two different light sources test.....	30
18 Two small buildings coated with different paint system and one uncoated building	31
19 An air conditioner (22000 BTU).....	32
20 Cable of thermocouple (K type).....	32
21 Data logger	32
22 Electrical Meter	33

LIST OF FIGURES (CONT.)

Figures	Pages
23 High solar reflective paint (Beger Cool UV Shield)	33
24 Cup anemometer.....	33
25 The position of top view to measure	34
26 The position of side view to measure.....	34
27 Simulation wall has size 3 mm. thickness that is used to analyze, coated with 1 mm of paint on both outside and inside building surface	40
28 The arrangement of wall and defined boundary condition.....	40
29 Flow Chart of Methodology	44
30 (a) The effect of building location on envelop surface and of room temperature (Based case) at center of the room	49
31 (b) The effect of building location on envelop surface and of room temperature (Based case) at the outside roof surface of room	50
32 (c) The effect of building location on envelop surface and of room temperature (Based case) at the outside roof surface on the first day.....	50
33 (d) The effect of building location on envelop surface and of room temperature (Based case) at the center of room	51
34 (a) Comparing envelop at the outside roof surface show room temperature of small building coated with high solar reflective paint, conventional color and uncoated.....	52
35 (b) Comparing envelop at the inside roof show surface room temperature of small building coated with high solar reflective paint, conventional color and uncoated.....	52
36 (c) Comparing envelop at the outside eastern wall surface show room temperature of small building coated with high solar reflective paint, conventional color and uncoated.....	53

LIST OF FIGURES (CONT.)

Figures	Pages
37 (d) Comparing envelop at the inside eastern wall surface show room temperature of small building coated with high solar reflective paint, conventional color and uncoated	53
38 (e) Comparing envelop at the center of room show room temperature of small building coated with high solar reflective paint, conventional color and uncoated	54
39 (f) Comparing envelop at the outside roof surface show room temperature of small building coated with high solar reflective paint, conventional color and uncoated	54
40 (g) Comparing envelop at the inside roof surface show room temperature of small building coated with high solar reflective paint, conventional color and uncoated	55
41 (h) Comparing envelop at the outside eastern wall surface show room temperature of small building coated with high solar reflective paint, conventional color and uncoated	55
42 (i) Comparing envelop at the inside eastern wall surface show room temperature of small building coated with high solar reflective paint, conventional color and uncoated	56
43 (j) Comparing envelop at the of the room show room temperature of small building coated with high solar reflective paint, conventional color and uncoated	56
44 The percentile of thermal reflectance and emittance of different type of paint.....	57
45 The comparing percentile of saving energy of small building coated with white and white grey color	58
46 Representations a comparison between overall heat transfers in to the building painted with Beger Cool, conventional paint, and no coating	60

LIST OF FIGURES (CONT.)

Figures	Pages
47 (a) Comparing outside wall temperature surface of numerical and experimental result	64
48 (b) Comparing inside wall temperature surface of numerical and experimental result	64
49 (c) Comparing outside wall temperature surface of numerical and experimental result	65
50 (d) Comparing inside wall temperature surface of numerical and experimental result	65