

## ภาคผนวก ข

การเปลี่ยนหน่วยใน Storage Routing Model

$$q_h = \frac{3.6}{A} Q$$

$$q_d = \frac{86.4}{A} Q$$

$q_h$  : runoff depth (mm/hr)  
 $A$  : drainage area (km<sup>2</sup>)  
 $Q$  : discharge (m<sup>3</sup>/s)

$q_d$  : runoff depth (mm/day)  
 $A$  : drainage area (km<sup>2</sup>)  
 $Q$  : discharge (m<sup>3</sup>/s)

$$\begin{cases} ds_h / dt_h = r_h - q_h - b_h \\ s_h = k_{h1} q_h^{p_1} + k_{h2} \frac{d}{dt_h} (q_h^{p_2}) \\ b_h = k_{h3} q_h \end{cases}$$

$$\begin{cases} ds_d / dt_d = r_d - q_d - b_d \\ s_d = k_{d1} q_d^{p_1} + k_{d2} \frac{d}{dt_d} (q_d^{p_2}) \\ b_d = k_{d3} q_d \end{cases}$$

$s_h$  : storage [mm]  
 $t_h$  : time [hr]

$s_d$  : storage [mm]  
 $t_d$  : time [day]

$b_h$  : loss depth [mm/hr]

$b_d$  : loss depth [mm/day]

$$p_1 = 0.6, \quad p_2 = 0.4648$$

$$p_1 = 0.6, \quad p_2 = 0.4648$$

$k_{h1}, k_{h2}, k_{h3}$  : storage coefficients using units  
 using units  
 of [mm] and [hr]  
 [day]

$k_{d1}, k_{d2}, k_{d3}$  : storage coefficients  
 using units  
 of [mm] and  
 [day]

$$\begin{cases} k_{h1} = C_{h1} A^{0.24} \\ k_{h2} = C_{h2} k_{h1}^2 (\bar{r}_h)^{-0.2648} \\ C_{h3} = k_{h3} + 1 \end{cases}$$

$$\begin{cases} k_{d1} = C_{d1} A^{0.24} \\ k_{d2} = C_{d2} k_{d1}^2 (\bar{r}_d)^{-0.2648} \\ C_{d3} = k_{d3} + 1 \end{cases}$$

$\bar{r}_h$  : average rainfall intensity [mm/hr]     $\bar{r}_d$  : average rainfall intensity [mm/day]

$C_{h1}, C_{h2}, C_{h3}$  : unknown coefficients

$C_{d1}, C_{d2}, C_{d3}$  : unknown coefficients

$$C_{d1} = \frac{C_{h1}}{(24)^{p_1}} = \frac{C_{h1}}{(24)^{0.6}} = 0.1486 C_{h1}$$

$$C_{d2} = C_{h2} \quad C_{d3} = C_{h3}$$