

เอกสารอ้างอิง

1. Zhang, G. and Schlarb, A.K., 2009, “Morphologies of the wear debris of polyetheretherketone produced under dry sliding conditions: Correlation with wear mechanisms”, **Wear**, Vol. 266, pp. 745-752.
2. Gwidon, S. and Andrew, B., 2001, **Engineering Tribology**, 2nd ed., Butterworth Heinemann, Oxford, pp. 484, 509-511, 554, 601 – 603.
3. Hong-Bin, Q, Qiang, G., Ai-Guo, T., Guo-Liang, P. and Le-Bo, X., 2007, “A study on friction and wear characteristics of nanometer Al_2O_3 /PEEK composites under the dry sliding condition”, **Tribology International**, Vol. 40, pp. 105-110.
4. Fu, H., Liao, Bo., Fangjuan, Q., Bao-Chen, S., Ai-Ping, L., and De-Liang, R., 2008, “The application of PEEK in stainless steel fiber and carbon fiber reinforced composites”, **Composites: B Engineering**, Vol. 39, pp. 585-591.
5. Wang, Q., Xue, Q., Liu, H., Shen, W. and Xu, J., 1996, “The effect of particle size of nanometer ZrO_2 on the tribological behaviour of PEEK”, **Wear**, Vol. 198, pp. 216-219.
6. Zhang, G., Schlarb, A., Tria, S. and Elkedim, O., 2008, “Tensile and tribological behaviors of PEEK/nano- SiO_2 composites compounded using a ball milling technique”, **Composites Science and Technology**, Vol. 68, pp. 3073-3080.
7. Davim, J. P. and Cardoso, R., 2009, “Effect of the reinforcement (carbon or glass fibres) on friction and wear behavior of the PEEK against steel surface at long dry sliding”, **Wear**, Vol. 13, pp. 795–799.
8. Erdemir, A., 2001, **Modern Tribology Handbook**, CRC Press., Oxford. No. 2.
9. Kimura, Y., Wakabayashi, T., Okada, K., Wada, T. and Nishikawa, H., 1999, Boron nitride as a lubricant additive, **Wear**, Vol. 232, pp. 199-206.

10. Pawlaka, Z., Kaldonski, T., Paid, R., Bayraktas, E., and Oloyede, A., 2009, “A comparative study on the tribological behaviour of hexagonal boron nitride (h-BN) as lubricating micro-particles-an additive in porous sliding bearings for a car clutch”, **Wear**, Vol. 267, pp. 1198-1202.
11. Tharajak, J., Palathai T. and Sombatsompop, N., 2011, “Effect of h-BN content on tribology behavior of PEEK composite coating”, **International Conference on Material Processing Technology**, June 2-3, Phuket, Thailand., pp. 317-321.
12. Brydson, J.A., 2000, **Plastics Materials**, 7th ed., Butter Heinemann, Oxford, pp. 247-509.
13. Bryan, H., 1999, **Engineering Composite Materials**, The Institute of Material, London, pp. 5-31.
14. อรุยา สรวารี, 2546, **สารเติมแต่งพอลิเมอร์ เล่ม 1**, พิมพ์ครั้งที่ 1, โรงพิมพ์แห่งจุฬาลงกรณ์มหาวิทยาลัย, กรุงเทพฯ, หน้า 8
15. Callister, D., 2007, **Material Science and Engineering : An introduction**, 7th ed., John Wiley & Sons Inc., New York. pp. 577 – 578.
16. Chawla, K. K., 2001, **Fibrous reinforcements for composites: overview” in encyclopedia of materials : science and technology**, Amsterdam : Elsevier, pp. 3160-3167.
17. Bader , M. G., 2000, **“The Composites Market” in Comprehensive Composite Materials**, Amsterdam: Elsevier, , pp. 1-13.
18. Gwidon, W.H., 2006, **Wear – materials, Mechanism and Practice**, 1st ed., John Wiley & Sons Ltd, pp. 270-290.
19. วิลเลียม เอฟ สมิท, 2547, **วัสดุวิศวกรรม**, สำนักพิมพ์ท้อป, กรุงเทพฯ, หน้า 273.
20. Wang, Q., Xue, Q., Shen, W., 1997 “The friction and wear properties of nanometre SiO₂ filled polyetheretherketone”, **Tribology International**, Vol.30, pp. 1997.

21. Spacialchem, S.A., n.d., **Adhesion guide: Adhesion theory** [Online], Available:
<http://www.specialchem4adhesive.com/resources/adhesionguide/index.aspx?id=theory2> [2011, July 2].

22. Spacialchem, S.A., n.d., **Adhesion guide: Adhesion theory** [Online], Available:
<http://www.specialchem4adhesive.com/resources/adhesionguide/index.aspx?id=theory5> [2011, July 2].

23. Spacialchem, S.A., n.d., **Adhesion guide: Adhesion theory** [Online], Available:
<http://www.specialchem4adhesive.com/resources/adhesionguide/index.aspx?id=theory6> [2011, July 2].

24. Spacialchem, S.A., n.d., **Adhesion guide: Adhesion theory** [Online], Available:
<http://www.specialchem4adhesive.com/resources/adhesionguide/index.aspx?id=theory3> [2011, July 2].

25. Spacialchem, S.A., n.d., **Adhesion guide: Adhesion theory** [Online], Available:
<http://www.specialchem4adhesive.com/resources/adhesionguide/index.aspx?id=theory4> [2011, July 2].

26. Hong-Bin, Q, Qiang, G., Ai-Guo, T., Guo-Liang, P. and Le-Bo, X., 2007, “A study on friction and wear characteristics of nanometer Al_2O_3 /PEEK composites under the dry sliding condition”, **Tribology International**, Vol. 40, pp. 105-110.

27. Almajid, A., Friedrich, K., Floeck J. and Burkhart, T., 2011, “Surface damage characteristics and specific wear rates of a new continuous carbon fiber (CF) / polyetheretherketone (PEEK) composite under sliding and rolling contact conditions”, **Applied Composite Material**, Vol.18, No. 3, pp. 211-230.

28. 2553, **PEEK** [Online], <http://en.wikipedia.org/wiki/PEEK#Properties>.

29. Goyal, R., Tiwari, A. and Negi, Y.S., 2008, "High performance nanocomposites for tribological applications: Preparation and characterization", **Materials Science and Engineering A**, Vol. 486, pp. 602 –610.
30. Harsha, A.P. and Tewari, U.S., 2002, 'Triboperformance of polyetheretherketone composites", **Polymer Testing**, Vol.21, pp.679-709.
31. Rajnesh, T., Xiong, D., Li, J. and Dai, J., 2008, "Elevated temperature tribological behavior of Ni based composites containing nano-silver and h-BN", **Wear**, Vol. 369, pp. 884 –890.
32. Westergard, R., Ahin, A., Axen, N., and Hogmark, S., 1998, 'Sliding wear and friction of Si_3N_4 – SiC- based ceramic composites containing hexagonal boron nitride", **Engineering Tribology**, Vol. 212, pp. 381-387.
33. Du, L., Zhang, W., Liu, W. and Zhang, J., 2010, Preparation and characterization of plasma sprayed NiAl-hBN composite coating, **Surface and Coating Technology**, Vol. 205, pp. 2419-2424.
34. Denton, R.M., and Fang, Z., 1995, **Rock bit grease composition**, U.S. Patent, No. 5589443.
35. Buckley, D., 1987, 'Friction and transfer behavior of pyrolytic boron nitride in contact with various metal" **ASLE transactions**, Vol. 21, pp.118-124.
36. Donnet, C., 1995, Advanced solid lubricant coating for high vacuum environments, **Surface and Coating Technology**, Vol. 80, pp. 151-156.
37. 2555, Carbon nanotube [Online], <http://coecs.ou.edu/Brian.P.Grady/nanotube.html>.
38. 2554, Carbon nanotube [Online], Available: www.rmutphysics.com.
39. Chen, W.X., Li, F., Han, G., Xia, J., Wang, L., J. Tu, T. and Xu, Z., 2003, "Tribology behavior of carbon-nanotube-filled PTFE composites", **Tribology Letters**, Vol. 15, No. 3, pp. 275-278.

40. Donnet, C., Le Mogne, Th., and Martin, J.M., 1993, "Superflow friction of oxygen-free MoS₂ coatings in ultrahigh vacuum", **Surface Coating Technology**, Vol. 62, pp. 406-411.
41. Gwidon, S. and Andrew, B., 2001, **Solid lubrication and surface treatments ; Engineering tribology**, 2nd ed., Butterworth Heinemann, Oxford, pp. 411 – 420.
42. Erdemir, A., 1995, "**Lubrication from mixture of boric acid with oils and greases**", U.S. patent, No. 5, pp. 431-830.
43. Martin, J.M., Pascal, H., Donnet, C., LeMogne, T., Loubet, J.L., and Epicier, T., 1994, "Superlubricity of MoS₂: crystal orientation mechanisms", **Surface Coating Technology**, Vol. 68-69, pp. 427-432.
44. Donnet, C., Le Mogne, Th., and Martin, J.M., 1993, "Superflow friction of oxygen-free MoS₂ coatings in ultrahigh vacuum", **Surface Coating Technology**, Vol. 62, pp. 406-411.
45. Sliney, H.E., 1982, "Solid lubricant materials for high temperatures", **A review, Tribology International**, Vol. 15, pp. 293-302.
46. Bharat, B., 1999, **Principles and applications of tribology**, 1st ed., John Wiley & Sons Inc., New York. pp. 577 – 578.
47. Briscoe, B. J. and Sinha, S. K., 2002, "Wear of polymers", **Proceeding of The Institution of Mechanical Engineering: Part J : Journal of Engineering Tribology**, Vol. 216, pp. 401-413.
48. Friedrich, K., Lu, Z. and Hager, A. M., 1995, "Recent advances in polymer composites", **Wear**, Vol. 190(2), pp. 139–144.

49. Brian, J. and Sujeet, K., 2001, Tribological applications of polymers and their composites : past, present and future Prospects ; 2nd ed., **Tribology of Polymeric Nanocomposites**, pp. 1 – 14.
50. Stachowiak, G.W. and Batchelor, A.W., 2001, **Engineering Tribology**, 2nd ed., Butterworth Heinemann, U.S.A., pp. 483-484, 537-538 , 542-544, 553-554.
51. Briscoe, B.J., 1993, The Tribology of composites materials : **A Preface, Advance in Composites Tribology** (ed. K. Friedrich), Elsevier, Amsterdam, pp 3-15.
52. Bely, V.A., Sviridenok, A.I., Petrokovets, M.I. and Savkin, V.G., 1982, “Friction and wear in polymer based materials”, **Pergamon Press**, Oxford, pp. 415.
53. Bhushan, B. and Gupta, B.K., 1991, **Wear: Handbook of tribology materials**, McGraw-Hill, Inc., U.S.A., pp 497-509
54. 2555, Wear [Online], <http://www.gordonengland.co.uk/wear.htm>.
55. Krueger F.E., 1975, “Fretting failures”, **Failure analysis and prevention, metals handbook**, Vol.10, 8th ed, American Society of metals, U.S.A., pp.154-155
56. Bhushan, B., 1999, **Principle and applications of tribology**, John wiley&sons, U.S.A., pp. 532-539.
57. Sinha, S.K., 2002, **ASM Handbook : Wear failures of plastics**, ASM International, Ohio, pp. 1019-1027.
58. Ramond, G., 2004, **Mechanical wear fundamentals and testing**, 2th ed., Marcel Dekker, New York, pp. 287.

59. Gardos, M.N., 1986, "Self-lubricating composites for extreme environmental conditions in friction and wear of polymer composites", **Composites Materials**, Friedrich, K. and Pipes, R.B., Elsevier, New York, , pp. 397–447.
60. Bhushan, B., 1999, **Principles and applications of tribology**, John Wiley & Sons, U.S.A., pp. 480-482.
61. Friedrich, K., Zhang Z. and Schlar, A., 2005, "Effects of various fillers on the sliding wear of polymer composites", **Composites Science and Technology**, Vol. 65, pp. 2329–2343.
62. Rong, M., Zhang, M., Liu, H., Zeng, H., and Friedrich, B., 2001, "Microstructure and tribological behavior of polymeric nanocomposites", **Industrial Lubrication and Tribology**, Vol. 53, pp. 72-77.
63. Zhong, Z., and Klaus, F., 2001, "Tribological characteristics of micro and nanoparticle filled polymer composites", **Polymer Composites : From Nano – to Macroscale** [Electronic], pp. 170-185, Available : Institutute for composites material 2012 October 1.
64. Li, F., Hu, K., Li, J., and Zhao, B., 2001, "The friction and wear characteristics of nanometers ZnO filled polytetrafluoroethylene", **Wear**, Vol. 249, pp. 877-882.
65. Sawyer, W.G., Freudenberg, K.D., Bhimaraj, P., and Schadler, L.S., 2003, "A study on the friction and wear behavior of PTFE filled with alumina nanopaticles", **Wear**, Vol. 254, pp. 573-580.
66. Chen, W.X., Li, F., Han, G., Xia, J.B., and Wang, L.Y., 2003, "Tribological behavior of carbon-nanotube-filled PTFE composites", **Tribology Letter**, Vol. 15, pp. 275-278.
67. Lai, S.Q., Li, T.S., Lui, X.J., and Lv, R.G., 2004, "A study on the friction and wear behavior of PTFE filled with acid treated nano-attapulgate", **Macromolecular Master.**, Vol. 289, pp. 916-922.

68. Rong, M.Z., Zhang, M.Q., Liu, H., Zeng, H., and Wetzel, B., 2001, "Microstructure and tribological behavior of polymeric nanocomposites", **Lubrication Tribology**, Vol. 53, pp. 72-77.
69. Wetzel, B., Hauptert, F., Friedrich, K., Zhang, M.Q., and Rong, M.Z., 2002, "Impact and wear resistance of polymer nanocomposites at low filler content", **Polymer Engineer and Science**, Vol. 42, pp. 1919-1927.
70. Wetzel, B., Hauptert, F., and Zhang, M.Q., 2003, "Epoxy nanocomposites with high mechanical and tribological performance", **Composites Science Technology**, Vol. 63, pp. 2055-2067.
71. Shi, G., Zhang, M.Q., Rong, M.Z., Wetzel, B., and Friedrich, K., 2003, "Friction and wear of low nanometer Si_3N_4 filled epoxy nanocomposites", **Wear**, Vol. 254, pp. 784-796.
72. Wang, Q., Xu, J., Shen, W., and Liu, W., 1996, "An investigation of the friction and wear properties of nanometer Si_3N_4 filled PEEK", **Wear**, Vol. 196, pp. 82-86.
73. Wang, Q., Xue, Q., Shen, W., and Xu, J., 1996, "The effect of particle size of nanometer ZrO_2 on the tribological behavior of PEEK", **Wear**, Vol. 198, pp. 216-219.
74. Wang, Q., Xue, Q., and Shen, W., 1997, "The friction and wear properties of nanometer SiO_2 filled PEEK", **Tribology International**, Vol. 130, pp. 193.
75. Wang, Q., Xu, J., Shen, W., and Xue, Q., 1997, "The effect of nanometer SiC filler on the tribological behavior of PEEK", **Wear**, Vol. 209, pp. 316-321.
76. Werner, P., Altstadt, V., Jaskulka, R., and Jacobs, O., 2004, "Tribological behavior of carbon-nanofibre-reinforced poly(ether ether ketone)", **Wear**, Vol. 257, pp. 1006-1014.
77. Qiao, H.B., Gao, Q., Tian, A.G., Pan, G.L., and Xu, L.B., 2007, "A study on friction and wear characteristics of nanometer Al_2O_3 /PEEK composites under the dry sliding condition", **Tribology International**, Vol. 140, pp. 105-110.

78. Shao, X., liu, W., and Xue, Q., 2004, “The tribological behavior of micrometer and nanometer TiO₂ particles filled poly(phthalazine ether sulfone ketone)”, **Apply Polymer Science**, Vol. 92, pp. 906-914.
79. Zoo, Y.S., An, J.W., Lim, D.P., and Lim, D.S., 2004, “Effect of carbon nanotube addition on tribological behavior of UHMWPE”, **Tribology Letter.**, Vol. 16, pp. 305.
80. ปัทม์ชนิต แสนวิทยากร, 2549, การศึกษาการเคลือบพอลิเมอร์ลงบนผิวชิ้นงานโลหะโดยกระบวนการพ่นเคลือบด้วยเปลวความร้อน, วิทยานิพนธ์ปริญญาวิศวกรรมศาสตรมหาบัณฑิต สาขาวิชาเทคโนโลยีวัสดุ คณะพลังงานสิ่งแวดล้อมและวัสดุ มหาวิทยาลัยเทคโนโลยีพระจอมเกล้าธนบุรี, หน้า 54.
81. ณัฐินี อินทวงศ์, 2552, อิทธิพลของสารเสริมแรงซิลิกอนไดออกไซด์-อะลูมิเนียมออกไซด์และถ่านลอยในผิวเคลือบวัสดุเชิงประกอบพอลิอีเทอร์อีเทอร์คีโตนต่อโครงสร้างและการต้านทานการสึกหรอ, วิทยานิพนธ์ปริญญาวิศวกรรมศาสตรมหาบัณฑิต สาขาวิชาเทคโนโลยีวัสดุ คณะพลังงานสิ่งแวดล้อมและวัสดุ มหาวิทยาลัยเทคโนโลยีพระจอมเกล้าธนบุรี หน้า 56.
82. นริศดา น้อยคำ, 2554, ผลของถ่านลอยจากโรงไฟฟ้าจังหวัดลำปาง ราชบุรี และระยอง ที่มีผลต่อสมบัติเชิงกลและความต้านทานการสึกหรอของวัสดุเชิงประกอบพอลิอีเทอร์อีเทอร์คีโตน, วิทยานิพนธ์ปริญญาวิศวกรรมศาสตรมหาบัณฑิต สาขาวิชาเทคโนโลยีวัสดุ คณะพลังงานสิ่งแวดล้อมและวัสดุ มหาวิทยาลัยเทคโนโลยีพระจอมเกล้าธนบุรี, หน้า 65-68.
83. Sujeet, K., and Brain, J., 2009, “Adhesion and friction of polymer” **Polymer Tribology**, World Scientific Publishing Co. Pte. Ltd., London, pp. 20-25.
84. Lieng-Hisang, L., 1985, **Polymer wear and Its control**, American chemical society, Washington,D.C., pp. 150-155.
85. Wang, Q., Xu, J., Shen, W. and Lui, W., 1996, “An investigation of the friction and wear properties of nanometer Si₃N₄ filled PEEK”, **Wear**, Vol. 196, pp. 82-86.

86. ปนัดดา นิรนาทล้ำพงศ์, John P.H., ผกามาศ แซ่หว่าง, วารุณี เปรมานนท์, สุรพล ราษฎร์นุ้ย และ สิทธิชัย วิโรจน์ปัทม์ภัม 2545, “การสึกหรอ: ความรู้เบื้องต้นและการป้องกัน”, ศูนย์เทคโนโลยี และวัสดุแห่งชาติ, หน้า 15-18.
87. Graldine, T. and Thomas, G., 2010, “Friction and wear of PEEK composites in vacuum environment”, **Wear**, Vol. 269, pp. 278 –284.
88. Long, C. and Wang, X., 2004, “Wear and mechanical properties of Ekonol/G/MoS₂/PEEK composites”, **Journal of Materials Science**, Vol. 39, pp. 1499 –1501.
89. Wang, Q., Jinfen, X., Weichang, S., and Weimin, L., 1996, “An investigation of the friction and wear properties of nanometer Si₃N₄ filled PEEK”, **Wear**, Vol. 196, pp. 82 –86.
90. Wang, Q., Jinfen, X., Weichang, S., and Weimin, L., 1997, “The effect of nanometer SiC filler on the tribological behavior of PEEK”, **Wear**, Vol. 209, pp. 316 –321.
91. Wang, Q., Jinfen, X., Weichang, S., and Weimin, L., 1996, “The effect of particle size of nanometer ZrO₂ on the tribological behavior of PEEK”, **Wear**, Vol. 198, pp. 216 –219.
92. Mishra, T.K., Kumar, A., Verma, V., Pandey, K.N., and Kumar, V., 2012, “PEEK composites reinforced with zirconia nanofiller”. **Composites Science and Technology**, Vol.72, pp. 1627–1631.
93. “Boron nitride finds new applications in thermoplastic compound”, 2008, **Plastics additives & compounding** [Electronic], pp. 26-31, Available : Elsevier Ltd. [2012, October 5].
94. Kuo, M.C., Tsai, C.M., Huang, J.C. and Chen, M., 2005, “PEEK composites reinforced by nano-sized SiO₂ and Al₂O₃ particulates”. **Materials Chemistry and Physics**, Vol.90 , No. 2, pp. 185–195.

95. Wang, L., Weng, L., Song, S. and Sun, Q., 2010, “Mechanical properties and microstructure of polyetheretherketone-hydroxyl apatite nanocomposite materials”, **Materials Letters**, Vol.64, pp.2201–2204.
96. Lai, Y.H., Kuo, M.C., Huang, J.C., and Chen, M., 2007, “On the PEEK composites reinforced by surface-modified nano-silica”, **Materials Science and Engineering**, Vol.485, pp. 158–169.
97. Jansen, M., 2002, **High performance non-oxide ceramics II**, Springer, Berlin.No. 102.
98. Samyn, P., Daets, P., Schoukens, G., and Hendrickx, B., 2003, “Tribology behavior of pure and graphite-filled polyimides under atmospheric conditions”. **Polymer Engineering and Science**, Vol.43, pp. 1477-1487.
99. Tharajak, J., Palathai, T., and Sombatsompop, N., 2012, “Tribological properties of flame sprayed hexagonal boron nitride/polyetheretherketone coatings”. **Advanced Materials Research**, Vol.412, pp. 333-336.
100. นันทิยา ศีลาคุปต์, 2555, การสึกหรอของผิวเคลือบเชิงประกอบอะลูมิเนียมบรอนซ์/พอลิอีเทอร์อีเทอร์คีโตน/พอลิเตตระฟลูออโรเอทิลีนในสภาวะการลื่นไถลแบบแห้ง, วิทยานิพนธ์ปริญญาวิศวกรรมศาสตรมหาบัณฑิต สาขาวิชาเทคโนโลยีวัสดุ คณะพลังงานสิ่งแวดล้อมและวัสดุ มหาวิทยาลัยเทคโนโลยีพระจอมเกล้าธนบุรี หน้า 88-91.
101. Song, H., Zhang, Z., and Luo, Z., 2006, “Effects of solid lubricants on friction and wear behaviors of the phenolic coating under different friction conditions”, **Surface and Coating Technology**, Vol. 201, pp.2760-2767.
102. Yang, Z., Dong, B., Huang, Y., Liu, L., Yan, F. and Li, H., 2005, “Enhanced wear resistance and micro-hardness of polystyrene nanocomposites by carbon nanotube”, **Material Chemistry and Physics**, Vol. 94, pp.109-113.