

## CONTENTS

	<b>PAGE</b>
ABSTRACT	i
ACKNOWLEDGEMENTS	iv
CONTENTS	v
LIST OF TABLES	vii
LIST OF FIGURES	viii
LIST OF SYMBOLS	x
LIST OF TECHNICAL VOCABULARY AND ABBREVIATIONS	xi
 <b>CHAPTER</b>	
<b>1. INTRODUCTION</b>	<b>1</b>
1.1 Motivation	1
1.2 Objective	2
1.3 Scope of Study	2
1.4 Contribution	3
 <b>2. THEORETICAL ISSUE/RELATED WORK</b>	 <b>4</b>
2.1 Nanorobot	4
2.1.1 Nanocomponent	4
2.1.2 Nanorobot Application	8
2.2 Swarm Intelligence	13
2.2.1 Ant Colony Optimization	13
2.2.2 Artificial Bee Colony Algorithm	14
2.2.3 Particle Swarm Optimization	15
2.3 Platelet and Hemostasis Process	18
2.3.1 Thrombocytopenia	18
2.3.2 Hemostasis Process	19
 <b>3. METHODOLOGY/RESEARCH METHODS</b>	 <b>22</b>
3.1 Nanorobot Characteristics and Control Mechanism	22
3.1.1 Nanorobot Characteristics Design	22
3.1.2 Nanorobot Control Mechanism	24
3.1.3 Nanorobot System	26
3.2 Circulatory System Model	28
 <b>4. RESULTS AND DISCUSSION</b>	 <b>32</b>
4.1 System Setting	32
4.2 Experimental Results	36
4.2.1 The Effect of Varying Perception Range	36
4.2.2 The Effect of Varying Maximum Velocity	38
4.2.3 The Effect of Varying Response Speed	40
4.2.4 The Performance of Control Mechanism	42
4.2.5 The Performance of PSO Control Algorithm in Newtonian and Non-Newtonian Blood Model	44
 <b>5. CONCLUSION/SUGGESTION</b>	 <b>46</b>
 <b>REFERENCES</b>	 <b>48</b>

<b>APPENDIX A Experimental Results for Nanorobot Swarm System</b>	<b>PAGE</b>
<b>CURRICULAM VITAE</b>	<b>52</b>
	<b>58</b>

## LIST OF TABLES

<b>TABLE</b>		<b>PAGE</b>
2.1	The coagulation factors [36]	21
A.1	The accuracy results for the case of varying the perception range of nanorobots with random movement	53
A.2	The accuracy results for the case of varying the perception range of nanorobots with PSO1	53
A.3	The accuracy results for the case of varying the perception range of nanorobots with PSO2	53
A.4	The accuracy results for the case of varying the maximum velocity of nanorobots with random movement	54
A.5	The accuracy results for the case of varying the maximum velocity of nanorobots with PSO1	54
A.6	The accuracy results for the case of varying the maximum velocity of nanorobots with PSO2	54
A.7	The accuracy results for the case of varying the nanorobot execution time of nanorobots with random movement	54
A.8	The accuracy results for the case of varying the nanorobot execution time of nanorobots with PSO1	55
A.9	The accuracy results for the case of varying the nanorobot execution time of nanorobots with PSO2	55
A.10	The speed results for the case of varying the perception range of nanorobots with random movement	55
A.11	The speed results for the case of varying the perception range of nanorobots with PSO1	55
A.12	The speed results for the case of varying the perception range of nanorobots with PSO2	56
A.13	The speed results for the case of varying the maximum velocity of nanorobots with random movement	56
A.14	The speed results for the case of varying the maximum velocity of nanorobots with PSO1	56
A.15	The speed results for the case of varying the maximum velocity of nanorobots with PSO2	57
A.16	The speed results for the case of varying the nanorobot execution time of nanorobots with random movement	57
A.17	The speed results for the case of varying the nanorobot execution time of nanorobots with PSO1	57
A.18	The speed results for the case of varying the nanorobot execution time of nanorobots with PSO2	57

## LIST OF FIGURES

FIGURE	PAGE	
2.1	The images of DNA origami objects which (A) the 2D shapes of DNA origami which was taken by an atomic force microscopy (AFM) and (B) the 3D shapes of DNA origami which was taken by a transmission electron microscopy (TEM)	5
2.2	The open and close process of nanocage	5
2.3	The graph of average of velocities of bacteria microactuator (A) <i>Serratia marcescens</i> -actuated microrobot and (B) <i>Salmonella typhimurium</i> -actuated microrobot	6
2.4	(A) schematic diagrams and snapshot images of nanomotor array which synchronously rotate clockwise. The scale bars are 10 $\mu\text{m}$ and (B) the component of a nanomotor	7
2.5	The rotation controlled biomolecule releases nanodevice	8
2.6	Nanorobot model for Brain aneurysm	9
2.7	The damaged nerve	9
2.8	Nanorobot model for damaged nerve	10
2.9	The remote-controlled dental nanorobot	11
2.10	The self-adaptive behavior of ants, (a) the ants randomly go to seek for food sources; (b) ants follow a path between nest and food source; ants choose, with equal probability, whether to shortest or longest path; (c) the majority of ants have chosen the shortest path	14
2.11	The pseudocode of ABC algorithm.	15
2.12	The nature flocking of birds and fish schooling.	15
2.13	Some common neighborhood topologies.	16
2.14	The pseudocode of PSO algorithm.	17
2.15	The petechia on the patient's back and arms [32]	19
2.16	The primary hemostasis. Platelets adhere at the injured site by sticking to the exposed collagen. The activated platelets release many factors in order to form a platelet plug. The normal endothelium concurrently releases prostacyclin and nitric oxide to prevent the activated platelets from aggregating at the undamaged site [N1].	20
3.1	The algorithm of nanorobots for finding the wound.	24
3.2	The shear stress versus shear rate of Newtonian fluid (red long dashes) and non-Newtonian fluid (blue line)	29
3.3	The shear stress versus shear rate of non-Newtonian fluid: shear-thinning fluid (green dot), shear-thickening (purple dash dot) and viscoplastic and viscoelastic fluid (blue line)	30
3.4	The velocity profile of (a) Newtonian and (b) non-Newtonian fluid.	31
4.1	The dimension of blood vessel.	32
4.2	The coordination for blood vessel.	33
4.3	The dimension of the wound in this simulation.	33
4.4	The illustration of the blood vessel and the wound in this simulation.	33

<b>FIGURE</b>	<b>PAGE</b>
4.5 (A) The comparison between the size of a nanorobot and the blood vessel in ratio and (B) The comparison between the size of a nanorobot and the wound in ratio.	33
4.6 The nanorobots in different state.	35
4.7 The comparison of experimental results between random movement, PSO1 and PSO2 in non-Newtonian model for the variation of PRange: (A) the median wound coverage rate and (B) the mean number of iterations.	37
4.8 The comparison of experimental results between random movement, PSO1 and PSO2 in non-Newtonian model for the variation of VMax: (A) the median wound coverage rate and (B) the mean number of iterations.	39
4.9 The comparison of experimental results between random movement, PSO1 and PSO2 in non-Newtonian model for the variation of NRTime: (A) the median wound coverage rate and (B) the mean number of iterations.	41
4.10 The comparison of the mean number of iterations between random movement, PSO1 and PSO2 in non-Newtonian model for the variation of NRTime only when the wound coverage rate reaches 0.8 before 10,000 iterations.	42
4.11 The comparison of experimental results between random movement, PSO1 and PSO2 in non-Newtonian: (A) the median wound coverage rate and (B) the mean number of iterations.	43
4.12 The comparison of experimental results between PSO-based nanorobots in Newtonian model and PSO-based nanorobots in non-Newtonian model: (A) effect of varying perception range, (B) effect of varying maximum velocity and (C) effect of varying response speed.	45

## LIST OF SYMBOLS

SYMBOL		UNIT
$A_1$	The amplitude of the oscillating component	
$c_1$	The acceleration constants for personal knowledge	
$c_2$	The acceleration constants for social knowledge	
$C_A$	The concentration of the solute A	
$D_A$	The diffusion coefficient of solute A	$m^2/s$
$f_p$	The pulse frequency	
$J_0$	The Bessel function zero order of the first kind	
$m$	The consistency index	
$n$	The power law index	
$NRTIME$	The nanorobot execution time	s
$PRange$	The nanorobot perception ability	$\mu m$
$r$	The vertical position in the vessel	$\mu m$
$R$	The vessel radius	$\mu m$
$r_1$	The random number between 0 to 1	
$r_2$	The random number between 0 to 1	
$R_p$	The plug core radius	$\mu m$
$t$	Time	s
$V$	The blood velocity	mm/s
$V_{Max}$	The maximum velocity of nanorobots	mm/s
$v(t)$	The current velocity at time $t$	
$v(t + 1)$	The new velocity	
$x$	the distance from the activated nanorobot at the measurement position	
$x(t)$	The current Position at time $t$	
$x_i(t)$	Position of nanorobot/particle in dimensions at time $t$	
$x_{lbest}$	The local best position	
$x_{pbest}$	The personal best position	
$\chi$	The constriction coefficient	
$\gamma$	The shear rate	
$\tau$	The shear stress	Pa
$\tau_w$	The shear stress at wall	Pa
$\tau_y$	The yield stress	Pa
$\nu$	The viscosity	
$-\frac{dP}{dx}$	The pressure gradient.	
$\rho$	The blood density	

**LIST OF TECHNICAL VOCABULARY AND ABBREVIATIONS**

ABC	=	Artificial bee colony
ACO	=	Ant colony optimization
ADP	=	Adenosine diphosphate
AFM	=	an atomic force microscopy
BSA	=	bovine serum albumin
H-B model	=	Herchel-Bulkley model
HRP	=	horseradish peroxidase
PA	=	polystyrene microbeads
PSO	=	Particle swarm optimization technique
SI	=	swarm intelligence
ssDNA	=	the single stranded DNA
TEM	=	a transmission electron microscopy
TRE	=	target-responsive encapsulation
vWF	=	von Willebrand factor