

เอกสารอ้างอิง

อุกฤษณ์ วังมงคล, 2008, การพัฒนาโลหะจำรูปร่างมาประยุกต์ในงานวาล์วควบคุม, วิทยานิพนธ์ปริญญาวิศวกรรมศาสตรมหาบัณฑิต สาขาวิชาวิศวกรรมไฟฟ้า คณะวิศวกรรมศาสตร์ มหาวิทยาลัยเทคโนโลยีพระจอมเกล้าธนบุรี, หน้า 1-120.

C. Alippi, M. ROVERI, “An adaptive CUSUM-based test for signal change detection”, **Circuits and Systems, 2006. ISCAS 2006. Proceedings. 2006 IEEE International Symposium on**, Kos, Grecia, 21-24 May 2006, pp. 5752 - 5755.

Balle, P. and Fuessel, D., 2000, “Closed-loop fault diagnosis based on a nonlinear process model and automatic fuzzy rule generation”, **Engineering Application of Artificial Intelligent**, Vol. 13, pp. 695-704.

Bayart, M., 2003, “Smart devices for manufacturing equipment”, **Robotica**, Vol. 21, pp. 325-333.

Chiang, L.H., Russell, E. L. and Braatz, R.D., 2002, “Fault detection and diagnosis in industrial systems”, **In Analytical methods** , Springer, pp. 173-209.

Farias Nascimento, M.M.S. and Jose de Araujo, C., 2006, “Electro-Thermomechanical characterization of Ti-Ni shape memory alloy thin wires”, **Materials Research** , Vol. 9, pp. 15-19.

Gall, K., Yang, N., Sehitoglu, H. and Chumlyakov, Y.I., 2001, “Fracture of precipitated NiTi shape memory alloys”, **International Journal of Fracture** , Vol. 109, pp. 189-207.

Heath, R.A., 1982, “A Model for Signal Detection Based on an Adaptive Filter”, **Biological Cybernetics**, Vol. 45, pp. 95-100.

Hines, A., Gausman, T.J., Glime, W.H., Hill, S.H. and Rigby, B.S., 2002, **Smart memory alloy actuated fluid control valve**, United State, Patent No. US 6,464,200.

Isermann, R., 2005, “Model-based fault detection and diagnosis - status and application”, **Annual Reviews in Control** , Vol. 29, pp. 71-85.

J.S., Sakellariou and S.D., Fassois, 2002, “Nonlinear ARX (NARX) based identification and fault detection in a 2 DOF system with cubic stiffness”, in **Proceeding of ISMA**, Leuven Belgium.

Leontaritis, I.J. and Billing, S.A., 1985a, “Input-output parametric models for non-linear systems – Part I: deterministic non-linear systems”, **International Journal of Control**, Vol. 41, No. 2, pp. 303-328.

Leontaritis, I.J. and Billing, S.A., 1985b, “Input-output parametric models for non-linear systems – Part II: stochastic non-linear systems”, **International Journal of Control**, Vol. 41, No. 2, pp. 329-344.

Meier, H., Czechowicz, A. and Haberland, C., 2009, “Control loops with detection of inner electrical resistance and fatigue-behaviour by activation of NiTi-Shape memory alloys”, **ESOMAT 2009**, pp. 189-207.

Page, E.S., 1954, “Continuous inspection schemes”, **Biometrika**, Vol. 41, pp. 100-115.

Piroddi, L. and Spinelli, W., 2003, “An identification algorithm for polynomial NARX models based on simulation error minimization”, **International Journal of Control**, Vol. 76, No. 17, pp. 1767-1781.

Ryhanen, Jorma, 1999, “**Biocompatibility evaluation of nickel-titanium shape memory metal alloy**”, Ph.D. Thesis, Surgery, Faculty of Medicine, Oulu University, p. 27.

Tang, Meng and Koch, W. H., 2009, “An Intelligent Model based on TS NARX for Process Prediction and Diagnosis Rule Extraction”, **Proceeding of the the 2009 Sixth International Conference on Fuzzy Systems and Knowledge Discovery**, Vol. 6, pp. 91-95.

Venkatasubramanian, V., Rengaswamy, R., Yin, K. and Kavuri, S.N., 2003, “A review of process fault detection and diagnosis Part I: Quantitative model-based methods”, **Computers and Chemical Engineering** , Vol. 27, pp. 293-311.

Xie, J., Yan, G. Xie, K. and Lin, T.Y., 2007, “Neuro-Fuzzy Model-Based CUSUM Method Application in Fault Detection on An Autonomous Vehicle”, in **Proceedings of IEEE International Conference on Granular Computing 2007**, pp. 548–548 .

Zhao, Q. and Kinneart, M., 2009, “Statistical Properties of CUSUM Based Fault Detection Schemes for Fault Tolerant Control”, in **Proceedings of the 48th IEEE Conference on Decision and Control, 15-18 December 2009, Shanghai**, pp. 7831 - 7836.