

## LIST OF FIGURES

<b>FIGURE</b>	<b>PAGE</b>
2.1 The three isotopes of hydrogen, showing their protons (marked in yellow, with positive charge), neutrons (green, with no charge), and electrons (red, with negative charge) (Schmidt, 2005)	6
2.2 Simple phase diagram for hydrogen (Zuttel, 2003)	7
2.3 Thermodynamics of H <sub>2</sub> O and CO <sub>2</sub> electrolysis at 0.1 MPa (Jensen et al., 2008)	13
2.4 The schematic diagram of the electrolyte solution	15
2.5 The relationship between current and electrode potential in the electrolysis cell (AccessScience, 2013)	16
2.6 Relationship between solution resistance and cell geometry for two limiting cases of electrodes in contact with electrolytes (Zoski, 2007)	18
2.7 Effect of a potential change on the standard free energies of activation for oxidation and reduction (Bard and Faulkner, 2001) Note: The lower frame is a magnified picture of the boxed area in the upper frame	20
2.8 Proposed model of the double-layer region under conditions where anions are specifically adsorbed (Bard and Faulkner, 2001)	25
2.9 Potential profiles across the double-layer region in the absence of specific adsorption of ions (Bard and Faulkner, 2001)	26
2.10 Geometrical definitions of void fraction: local, chordal, cross-sectional and volumetric (Thome, 2010)	29
2.11 Components of the pulse signal	30
2.12 Stages 1-3 in the factor analysis decision diagram (Hair et al., 2006)	33
2.13 Stages 4-7 in the factor analysis decision diagram (Hair et al., 2006)	34
2.14 General model of a process or system (Montgomery, 2001)	36
3.1 Control volume of the electrochemical cell	43
3.2 The relationship between the solution temperature and the electrolyte conductivity	47
3.3 The relationship between the bubble size and the conductivity of the electrolyte	47

## LIST OF FIGURES (Continue)

<b>FIGURE</b>	<b>PAGE</b>
3.4 The relationship between the height of the electrodes and the conductivity of the electrolyte	48
3.5 Concentration of $K^+$ at surface electrode	49
3.6 Concentration of $OH^-$	50
3.7 Conductivity of $K^+$ and $OH^-$	51
3.8 Conductivity of KOH solution	51
3.9 Ionic resistances over time up to 8 hours	52
3.10 Diagram of experimental apparatus	53
3.11 Comparisons between experimental and modeling results	55
4.1 Diagram of experimental apparatus	58
4.2 Diagram of experimental apparatus with pumping	60
4.3 Diagram of experimental apparatus with function generator and IGBT	61
4.4 The result of Response Surface Regression: Potential (V) versus Current density (Amm-2) and Temperature (K)	63
4.5 The contour plots of a response surface of potential (V)	64
4.6 The result of Response Surface Regression: Rate (Lmin-1) versus Current density (Amm-2) and Temperature (K)	65
4.7 The contour of a response surface of gas production rate (Lmin-1)	65
4.8 Effect of Direct Current on hydrogen production rate and efficiency	66
4.9 Effect of duty cycle on hydrogen production rate a) 30 A, b) 40 A and c) 50A	67
4.10 Effect of duty cycle on efficiency a) 30 A, b) 40 A and c) 50 A	68
4.11 Effect of frequency on hydrogen production rate a) 30 A, b) 40 A and c) 50 A	70
4.12 Effect of frequency on hydrogen production rate at 50 A	71
4.13 Effect of frequency on efficiency a) 30 A, b) 40 A and c) 50 A	72
4.14 Voltage and current signal of experiment	73

## LIST OF FIGURES (Continue)

<b>FIGURE</b>	<b>PAGE</b>
4.15 Wave forms of IGBT gate voltage and output voltage a) 20 % duty cycle 1 Hz, b) 50 % duty cycle 1 Hz, c) 80 % duty cycle 1 Hz, d) 20 % duty cycle 5 Hz, e) 50 % duty cycle 5 Hz, f) 80 % duty cycle 5 Hz, g) 20 % duty cycle 10 Hz, h) 50 % duty cycle 10 Hz and i) 80 % duty cycle 10 Hz	74
4.16 Correlation of current density and potential	75
4.17 Relationship between power consumption and current density	76
4.18 Tenor of hydrogen production rate at varying temperature	76
4.19 Relationship between operating time and hydrogen production rate	77
4.20 Effect of temperature on hydrogen production rate of copper	78
4.21 Effect of temperature on hydrogen production rate of stainless steel	78
4.22 Relation of potential and current density	79
4.23 Difference of electrode materials on hydrogen production rate	79
4.24 Difference of electrode materials on efficiency	80
4.25 Current - gas production rate comparison of various pumping	81
4.26 Power consumption - gas production rate comparisons of various circulation	82
4.27 The result of Response Surface Regression: Rate (Lmin-1) versus Current density (Amm-2), Temperature (K), Frequency (Hz), Duty Cycle and %wt (moll-1)	83
B.1 Diagram of experimental apparatus	102
B.2 The result of Response Surface Regression: Rate (Lmin-1) versus Current density (Amm-2), Distance (mm) and Concentration (moll-1)	104
B.3 The result of Response Surface Regression: Rate (Lmin-1) versus Current density (Amm-2) and Concentration (moll-1)	105
B.4 The mean hydrogen production rate on the y axis by varying the concentration on the x axis	105
B.5 The contour of a response surface of hydrogen production rate (Lmin-1)	106

**LIST OF FIGURES (Continue)**

<b>FIGURE</b>		<b>PAGE</b>
B.6	The result of Response Surface Regression: Rate (Lmin-1) versus Current density (Amm-2), Distance (mm) and Concentration (moll-1)	107
B.7	The result of Response Surface Regression: Rate (Lmin-1) versus Current density (Amm-2) and Concentration (moll-1)	107
B.8	The mean hydrogen production rate on the y axis by varying the concentration on the x axis	108
B.9	The contour of a response surface of hydrogen production rate (Lmin-1)	109
B.10	Effect of concentration on hydrogen production rate	109
B.11	Sediments in NaCl electrolyte	111
B.12	Direction of corrosion on the anode side	112
B.13	Outside of Anode	112
B.14	Inside of Anode	113