

## LIST OF FIGURES

FIGURE		PAGE
2.1	Structure of $\alpha$ alumina. On the left, seen in the base plan: the large circles represent the anions, the small full circles the cations, the small empty circles the vacant octahedral interstices. On the right, the view of the cation sublattice: the full circles represent the full cations and the circles the vacant sites	9
2.2	Single-mesh discharge circuit	12
2.3	Variation of reflectivity with wavelength for several metallic materials. The wavelengths of two important lasers (Nd:YAG and CO <sub>2</sub> ) are superimposed on the figure	14
2.4	Variation of reflectivity with temperature for 1.06 $\mu$ m radiation	15
2.5	Various effects of laser-material interaction (a) heating, (b) surface melting, (c) surface vaporization, (d) plasma formation, and (e) ablation	16
2.6	Regimes of various effects during laser-material interactions and their application in laser materials processing (pulsed laser ablation/deposition, PLA/PLD; laser annealing, LA; laser cleaning, LC; laser-induced isotope separation, LIS; multiphoton absorption/ionization, MPA/ MPI; laser-supported detonation/combustion waves, LSDW/LSCW; laser-induced CVD, LCVD; laser-induced electrochemical plating/etching, LEC; long pulse or CW CO <sub>2</sub> laser-induced reduction/oxidation, RED/OX	17
2.7	Schematic of the laser irradiation geometry and surface temperatures at various times: (a) initial condition with uniform temperature $T_0$ , throughout the material, (b) laser heating with surface temperature, $T_s > T_0$ , and (c) cooling stage (laser off) with surface temperature $T'_s < T_s$ (surface temperatures are less than melting point at all times)	19
2.8	Variation of calculated temperature increases with time at various depths during laser irradiation of copper using laser power density of $10^{10}$ W/m <sup>2</sup> and irradiation time of 1 $\mu$ s	21
2.9	Various mechanisms of laser ablation	21
2.10	Experimental setup for laser ablation of solids in a liquid environment	22

## LIST OF FIGURES (cont'd)

FIGURE		PAGE
2.11	Schematic drawing of a conventional SEM. The evacuated microscope column (inside the bold dashed frame) contains the electron gun, electromagnetic lenses, electromagnetic deflection coils, apertures, the specimen stage, and the detectors. The electronics console houses the power supplies for the acceleration voltage and the electromagnetic lenses, the scan generator, amplifiers for the signals, and monitors for display and recording of images. Modern SEMs are controlled by a PC. A, anode; BSE, backscattered electrons; C, cathode; ConA, condenser aperture; ConL, condenser lens; CL, cathodoluminescence; Defl . X, pair of beam deflection coils in the X direction; Defl . Y, pair of beam deflection coils in the Y direction; Det., detectors; DF-D, dark-field detector; O, specimen; OA, objective aperture; OL, objective lens; PC, personal computer; SE, secondary electrons; STEM, scanning transmission electron microscope signal; W, Wehnelt cylinder; X-ray, X-ray signal.	26
2.12	Schematic drawing of signals for a thin sample generated by the impinging electrons	27
2.13	Micrograph series of increasing magnification of the head and the eye of a fly, recorded with secondary electrons at 30 kV. The specimen was air dried and sputter coated with about 15 nm gold. Note the large depth of focus. The last magnification step from (e) to (f) barely reveals further fine details of the specimen because of the preparation used. The scale of dimensions of the micrographs covers about three orders of magnitude.	28
2.14	Geometrical arrangement of EDS in a scanning electron microscope (SEM)	29
2.15	Potential interference of X-ray detection due to low take-off angle in the SEM	29
2.16	Bragg diffraction by crystal planes. The path difference between beams 1 and 2 is $SQ + QT = 2 PQ \sin\theta$	30
2.17	The excitation process; $E =$ energy of photon (J), $h =$ Planck's constant ( $6.626 \times 10^{-34}$ J/s) and $\nu =$ frequency (Hz) of its associated electromagnetic wave	32

## LIST OF FIGURES (cont'd)

FIGURE		PAGE
2.18	Electronic energy levels and transitions	32
2.19	Electronic transitions with vibrational transitions superimposed. (Rotational levels, which are very closely spaced within the vibrational levels, are omitted for clarity)	33
2.20	Survey spectrum from Sn showing the XPS transitions accessible using $AlK\alpha$ radiation, the features marked with an asterisk are electron energy loss features due to plasmon excitation	36
2.21	Schematic diagram of the XPS process, showing photoionization of an atom by the ejection of a 1s electron	37
2.22	Photo electron spectrum of lead showing the manner in which electrons escaping from the solid can contribute to discrete peaks or suffer energy loss and contribute	38
3.1	Photograph of aluminum powder and aluminum pellet	39
3.2	Photograph of the Nd:YAG laser used in this study	39
3.3	Experimental setup for synthesizing $Al_2O_3$ nanoparticles by laser ablation of Al in deionized water	40
3.4	Field emission scanning electron microscope (FE-SEM)	41
3.5	X-ray diffractometer	41
3.6	UV-visible spectrophotometer	42
3.7	X-ray Photoelectron Spectroscopy	43
4.1	Laser energy of each voltage by adjusting pulse durations	44
4.2	Laser power output waveform of Nd:YAG laser at 300 V a) 1 ms b) 10 ms c) 20ms (1V/1kW)	45
4.3	Laser power output waveform of Nd:YAG laser at 400 V a) 1 ms b) 10 ms c) 20ms (1V/1kW)	46
4.4	Laser power output waveform of Nd:YAG laser at 500 V a) 1 ms b) 10 ms (1V/1kW)	47
4.5	Plot of coefficient of third equation in each voltage	48
4.6	RLC circuit simulation using MATLAB/Simulink	49
4.7	Trigger logic was performed to switch in RLC circuit	49
4.8	The simulation results of RLC model using MATLAB/Simulink at capacitor voltage 300 V 20 ms a) Voltage across capacitor b) Resistor voltage c) Resistor current d) Resistor power	50

## LIST OF FIGURES (cont'd)

FIGURE		PAGE
4.9	The simulation results of RLC model using MATLAB /Simulink at capacitor voltage 400 V 20 ms a) Voltage across capacitor b) Resistor voltage c) Resistor current d) Resistor power	51
4.10	The simulation results of RLC model using MATLAB/Simulink at capacitor voltage 500 V 20 ms a) Voltage across capacitor b) Resistor voltage c) Resistor current d) Resistor power	52
4.11	Approximation of pulsed power output to rectangular power output 20 ms in different voltages 300, 400, 500 V	53
4.12	Approximation of pulsed power output to rectangle power output 1J/pulse in different voltages	54
4.13	Approximation of pulsed power output to rectangular power output 3J/pulse in different voltages	54
4.14	Approximation of pulsed power output to rectangular power output 5J/pulse in different voltages	55
4.15	Simulation of heat at surface Al pellet from square power output 1J at 300, 400, 500 V	55
4.16	Simulation of heat at surface Al pellet from square power output 3J at 300, 400, 500 V	56
4.17	Simulation of heat at surface Al pellet from square power output 5J at 300, 400, 500 V	56
4.18	Plasma plume observed during laser ablation of aluminum target in liquid	57
4.19	Schematically mechanism of alumina nanoparticles generation by the laser ablation in a liquid (a) target surface was heated up by the laser beam, (b) plasma plume of alumina and shock wave were formed and condensed, and (c) alumina nanoparticles were generated.	58
4.20	FE-SEM images of (a) aluminum powder, and alumina nanoparticles at 300 V with different laser energies of (b) 1 J, (c) 3 J (d) 5 J and (e) 7 J.	60
4.21	Plot of particle size distribution of alumina nanoparticles at 300 V with different laser energies: (a) 1 J/pulse, (b) 3 J/pulse and (c) 5 J/pulse	62
4.22	FE-SEM images of alumina nanoparticles at 400 V with different laser energies of (a) 1 J, (c) 3 J and (d) 5 J.	64

## LIST OF FIGURES (cont'd)

FIGURE		PAGE
4.23	FE-SEM images of alumina nanoparticles at 500 V with different laser energies of (a) 1 J, (c) 3 J and (d) 5 J.	65
4.24	Plot of particle size distribution of alumina nanoparticles at 400 V with different laser energies: (a) 1 J/pulse, (b) 3 J/pulse and 500 V: (c) 1 J/pulse	66
4.25	FE-SEM images of alumina nanoparticles synthesized at 300 V, 1 J with different repetition rates: (a) 10 Hz and (b) 18 Hz	67
4.26	Plot of particle size distribution of alumina nanoparticles at 300 V, 1 J with different repetition rates (a) 10 Hz (b) 18 Hz	68
4.27	EDS results of laser energies 1, 3, 5 J at 300 V	69
4.28	Alumina nanoparticles dispersed in deionized water at 300V after 5000 pulses of laser ablation	70
4.29	Absorption spectra in deionized water with suspended alumina nanoparticles prepared from different laser energies of 1, 3 and 5 J.	70
4.30	Absorption spectra in deionized water with suspended alumina nanoparticles prepared from laser energy of 1 J	71
4.31	Absorption spectra in deionized water with suspended alumina nanoparticles prepared from laser energy of 3 J.	71
4.32	Absorption spectra in deionized water with suspended alumina nanoparticles prepared from laser energy of 5 J.	72
4.33	Linear relationship between the absorbance and the concentration at wavelength 210 nm.	72
4.34	XRD patterns of pure Al and Al <sub>2</sub> O <sub>3</sub> nanoparticles synthesized from laser energies of 1, 3, and 5 J.	75
4.35	XPS survey scans of different laser energies 1, 3 and 5 J	76
4.36	The analysis of Al <sub>2</sub> p at different energies 1, 3 and 5 J	77
4.37	The analysis of O <sub>1</sub> s at different energies 1, 3 and 5 J	77