

เอกสารอ้างอิง

- [1] C. Wagner, S. Lederman, and R. Howe, "A Tactile Shape Display Using RC Servomotors," 10th Symposium on Haptic Interface Environment and Tele operator, March, 2002.
- [2] M. Benali-Khoudja, M. Hafez, J. M. Alexandre, A. Kheddar, and V. Moreau, "VITAL: A New Low-Cost Vibro-TActiLe Display System," Proc. of IEEE International Conference on Robotics and Automation, 2004.
- [3] J. Pasquero and V. Hayward, "STReSS: A practical tactile display system with one millimeter spatial resolution and 700 Hz refresh rate," Proc. of Eurohaptics 2003, pp. 94-110, 2003.
- [4] G. Moy, C. Wagner, and R. Fearing, "A compliant tactile display for teletaction," Proc. of IEEE International Conference on Robotics and Automation, 2000.
- [5] K. Ikuta, "Micro/miniature shape memory alloy actuator," IEEE Robotics and Automation, pp. 2156-2161 1990.
- [6] R. Velazquez, E. Pissaloux, M. Hafez, and J. Szewczyk, "A low-cost highly-portable tactile display based on shape memory alloy microactuators," Proc. of IEEE International Conference on Virtual Environments, Human-Computer Interfaces and Measurement Systems, pp. 121-126, 2005.
- [7] Y. Haga, W. Makishi, K. Iwami, K. Totsu, K. Nakamura, and M. Esashi, "Dynamic Braille Display Using SMA Coil Actuator and Magnetic Latch," Sensors and Actuators A 119, pp. 316-322, 2005.
- [8] M. Sreekumar, M. Singaperumal, T. Nagarajan, M. Zoppi, and R. Molino, "Recent advances in nonlinear control technologies for shape memory alloy actuators " Journal of Zhejiang University - Science A, vol. 5, pp. 818-829, April, 2007.
- [9] K. Ikuta, M. Tsukamoto, and S. Hirose, "Shape memory alloy actuator system with electrical resistance feedback and application for active endoscope," Proc. IEEE Int. Conf. Robot. Automat, pp. 427-430, 1988.
- [10] K. Kuribayashi, "Improvement of the response of an SMA actuator using a temperature sensor," Int. J. Robot. Res, vol. 10, pp. 13-20, 1991.

- [11] S. Majima, K. Kodama, and T. Hasegawa, "Modeling of Shape Memory Alloy Actuator and Tracking Control System with the Model," *IEEE Transactions on Control Systems Technology*, vol. 9, January, 2001.
- [12] K. Ikuta, M. Tsukamoto, and S. Hirose, "Mathematical model and experimental verification of shape memory alloy for designing microactuator," in *Proc. IEEE Microelectromechanical*, pp. 103–108, 1991.
- [13] D. Madhill and D. Wang, "Modeling and stability of a shape memory alloy position control system," *IEEE Trans. Control Syst. Technol.*, vol. 6, pp. 473–481, Jul, 1998.
- [14] C. Liang and C. A. Roger, "One-dimensional thermo mechanical constitutive relations for shape memory materials," *Journal of Intelligent and Flexible Systems and Structures.*, pp. 207-234, 1990.