Thesis Title	Removal of Benzene by Living Plant, Plant Leaf and Biofilter
Thesis Credits	48
Candidate	Mr. Chairat Treesubsuntorn
Thesis Advisor	Assoc. Prof. Dr. Paitip Thiravetyan
Program	Doctor of Philosophy
Field of Study	Biotechnology
Department	Biotechnology
Faculty	School of Bioresources and Technology
Academic Year	2014

## Abstract

After screening 8 ornamental plants for 20 ppm benzene removal in a static system by Chamaedorea seifrizii, Scindapsus aureus, Sansevieria trifasciata, Philodendron domesticum, Ixoraebarbata craib, Monster acuminate, Epipremnum aureum, and Dracaena sanderiana found that D. sanderiana had the highest benzene removal efficiency of 20 ppm under 32 °C at 72 hours. In a long-term study, 4 cycles of benzene exposure were studied under both 24 hour dark and 24 hour light conditions. From the  $2^{nd}$  to  $4^{th}$  cycle, D. sanderiana growing under 24 hour light conditions had higher benzene removal efficiency than D. sanderiana growing under 24 hour dark conditions, and the closing of D. sanderiana stomata was found only in 24 hour dark conditions. At the final cycle, D. sanderiana still survived, and benzene uptake continued. From the calculation, 46% of benzene was taken up by D. sanderiana crude wax, while 54% of benzene was predicted to be taken up by the stomata at 72 hours. This result suggests that gaseous benzene phytoremediation is a sustainable technology. Due to high levels of benzene being taken up by crude wax, the application of plant wax for gaseous benzene adsorption was also studied. Twenty-one plant leaf materials such as Homalomena rubescens, Citrus hystrix, Musa paradisiaca, Mangifera indica, Catura metet, Lagerstroemia inermis, Cananga odorata, Cassia siamea, Bougain villea, Litchi chinensis, Coccinia grandis, Dieffenbachia picta, Attacus atlas, Polyalthia longifolia, Acrostichum aureum, Ficus religiosa, Alstonia scholaris, Anthurium andraeanum, Plerocarpus Indicus, Lagerstroemia macrocarpa, and Dracaena sanderiana were screened for benzene adsorption efficiency in a static system. The leaf materials from Dieffenbachia picta, Acrostichum aureum, Ficus religiosa, Lagerstroemia macrocarpa, Alstonia scholaris, and Dracaena sanderiana were found to have high potential for benzene removal. In addition, the relationship between quantity and composition of wax to benzene removal efficiency was also studied. The relationship between benzene adsorption and quantity of wax was found to be a logarithmic curve with  $R^2$ =0.65. Increasing crude wax can improve benzene adsorption, however, although high quantities of wax occurred in some leaf materials, low benzene removal was found to be significant if compared with other plant materials with the same wax quantity. For the composition of wax, alpha-linoleic acid and dodecyl cyclohexane were found to be the main composition in plant leaf materials with high benzene adsorption. This might also be a key factor for benzene removal. Therefore 15 g of 6 plant leaf materials with high gaseous

benzene adsorption such as *D. picta, A. aureum, F.religiosa, L. macrocarpa, A. scholaris* and *D.sanderiana* were applied in a continuous system. Glass beads with cassava glueimmobilized with leaf material were investigated in a continuous adsorption system with 3 min of retention time. In an adsorption system, *A. aureum* and *A. scholaris* leaf materials showed the highest benzene removal capacity, around 60-80% benzene removal for 120 h. Other leaf material from *D. picta, F.religiosa, L. macrocarpa,* and *D.sanderiana* can uptake benzene around 60-80%, but theses material was saturated with benzene in 102 h. Physical sorption was confirmed by hexane desorption and the FT-IR results. *A. aureum* and *A.* 

sorption was confirmed by hexane desorption and the FT-IR results. A. aureum and A. scholaris leaf cassava-bead immobilized with P. putida were used as a biofilter system. Retention time had been varied from 3 min to 0.5 min. The relationship between the loading rate and elimination capacity was also calculated. 10 g/m<sup>3</sup>/h had been known as a suitable loading rate. At 3 min of retention time, benzene was completely removed by biofilter, and also when retention time was decreased to be 1.2-1.5 min, biofilter can still remove benzene completely. The result suggested that 1.2-1.5 min of retention time with an enriched medium was a suitable condition for a biofilter system.

Keywords: Adsorption/ Benzene/ Biofilter/ Crude wax/ *Dracaena sanderiana/* Phytoremediation/ Plant leaf material