

ເອກສາຮ້າອ້າງອີງ

- [1] ປະກາສ ເຊື່ອງ “ວັດທະນາໄຟຟ້າ” <http://www.pea.co.th/Documents/Rate2012.pdf>
- [2] “ຄູ່ມືອກລາດຄ່າໄຟຟ້າ” ອ. ໄຊຍະ ແຫ່ມຫ້ອຍ
- [3] “ຄູ່ມືອກຈັດການພັບງານໄຟຟ້າໃນໂຮງງານ” ກຣມສ່າງເສີມອຸຕສາຫກຮຽມ ກຣທວງອຸຕສາຫກຮຽມ
- [4] ເອກສາປະກອບການອບຮມ ເຊື່ອງ “ການຕຽບຈັດແລກການຮັບຮັບມື້ອງມູລເພື່ອການອຸ່ນຮັກໜໍ່ພັບງານ” ສໍານັກງານເຖິງໂຄໂລຢີຄວາມປລອດກໍ່ ກຣມໂຮງງານອຸຕສາຫກຮຽມ ກຣທວງອຸຕສາຫກຮຽມ
- [5] M. Zucker and J. J. Erhart, “Capacitors near loads? The engineering viewpoint,” IEEE Trans. Ind. Appl., vol. IA, No. 2, pp. 308-317, Mar./Apr. 1985.
- [6] T. M. Blooming and D. J. Carnavale, “Capacitors Application Issues,” IEEE Trans. Ind. Appl., vol. 44, No. 4, pp. 1013-1026, Jul./Aug. 2008.
- [7] Paiko, “Installing power-factor improvement,” Plant Eng., pp. 78- 83, Jan. 11, 1979.
- [8] Gonen Turan, Electric Power Distribution System Engineering, McGraw-Hill, 1986.
- [9] A Report prepared by AEB, WAPDA for different cities. “To Improve Power Factor upto 0.95,1991.
- [10] “Power Factor Improvement in Industry”, by Khalid Perm Associate Jafii and Associates, “The Electrical Engineer”, Vo1.1 No.2-12, Sept.92 - July 93.
- [11] “Energy Conservation by Power Factor improvement in Pakistan”, by Dr. Sohail A Qureshi. University of Engineering and Technology, Lahore, Pakistan. Published in “The Electrical Engineer”, Vol. XXIV, April -.December 1993.
- [12] L. Korunovic and D. Stojanovic, “Load model parameters on low and middle voltage in distribution networks,” Elektroprivreda, 2002, (2), pp. 46–56.
- [13] J. Ribeiroand and F. Lange, “A new aggregation method for determining composite load characteristics,” IEEE Trans. Power System, 1982, Vol. 101 (3), pp. 2869–2875.
- [14] R. He, J. Ma and Hill David J, “Composite load modeling via measurement approach,” IEEE Trans Power System, 2006, Vol. 21(2), pp. 663–672.
- [15] T. Frantz, T. Gentile, , S. Ihara, N. Simons and M. Waldron, “Load behavior observed in LILCO and RG&E systems,” IEEE Trans. Power System, 1984, Vol. 103, (2), pp. 819–831
- [16] K. Tomiyama, J. P.Daniel, and S. Ihara, “Modeling air conditioner load for power system studies,” IEEE Trans. Power Syst., vol. 13, no. 2, pp. 414–421, May 1998.
- [17] V.Mullis, B. Nekooie, and J. Bright, “Economic analysis of distribution capacitor additions for leveling feeder voltage and voltage reductions,” Georgia Power Rep., 1999.

- [18] S. Civanlar and J. J. Grainger, “Vol/var control on distribution systems with lateral branches using shunt capacitors and voltage regulators, part III: The numerical results,” IEEE Trans. Power App. Syst., vol. PAS-104, pp. 3291–3297, Nov. 1985.
- [19] M. E. Baran and F. F. Wu, “Optimal sizing of capacitors placed on a radial distribution system,” IEEE Trans. Power Delivery, vol. 4, pp. 735–743, Jan. 1989.
- [20] H. D. Chiang, J. C. Wang, O. Cockings, and H. D. Shin, “Optimal capacitor placement in distribution systems; Part 1: A new formulation of overall problem,” IEEE Trans. Power Delivery, vol. 5, pp. 634–642, Apr. 1990.
- [21] “Optimal capacitor placement in distribution systems; Part 2: Solution algorithms and numerical results,” IEEE Trans. Power Delivery, vol. 5, pp. 643–649, Apr. 1990.
- [22] H. N. Ng, M. M. A. Salama, and A. Y. Chikhani, “Classification of capacitor allocation techniques,” IEEE Trans. Power Delivery, vol. 15, pp. 387–392, Jan. 2000.
- [23] R. A. Gallego, A. Monticelli and R. Romero, “Optimal capacitor placement in radial distribution networks”, IEEE Trans. Power System, 2001, 16, (4), pp. 630–637
- [24] K.R.C. Mamandur and R.D. Chenoweth, “Optimal Control of Reactive Power Flow for Improvements in Voltage Profiles and for Real Power Loss Minimization”. IEEE Transactions on PAS, Vol. PAS-100, No.7. July 1981. pp. 3185-3194.
- [25] T. H. Fawzi, S.M. El-Sobki and M.A. Abdel-Haliin, “New Approach for the Application of Shunt Capacitors to the Primary Distribution Feeders”, IEEE Transactions on PAS, Vol. PAS-102, No.1, January 1983, pp.10-13.
- [26] J. J. Grainger and S. H. Lee, “Optimum Size and Location of Shunt Capacitors for Reduction of Losses on Distribution Feeders”, IEEE Transactions on Power Apparatus and Systems, Vol. PAS-100. No.3, March 1981, pp.1105-1118.
- [27] IEEE Task Force on Load Representation for Dynamic Performance: ‘Bibliography on load models for power flow and dynamic performance simulation’, IEEE Trans. Power System, 1995, Vol. 10 (1), pp. 523–538.
- [28] IEEE Task Force on Load Representation for Dynamic Performance, “Load representation for dynamic performance analysis,” IEEE Trans Power System, 1993; Vol. 8(2), pp. 472–482.
- [29] CIGRE Task Force 38.02.05. Load modeling and dynamics. Electra, May 1990.
- [30] Y. Baghzouz and C. Quist, “Determination of static load models from LTC and capacitor switching tests’. Proc. IEEE PES Summer Meeting, July 2000, pp. 389–394
- [31] C. Concordia and S. Ihara, “Load representation in power system stability studies,” IEEE Trans. Power System, 1982, Vol. 101 (4), pp. 969–977.
- [32] C. W. Taylor, “Power system voltage stability” (McGraw-Hill, 1994)

- [33] L. Hajagos and B. Danai, “Laboratory measurements and models of modern loads and their effect on voltage stability studies”, IEEE Trans. Power System, 1998, Vol. 13 (2), pp. 584–592.
- [34] N. R. Watson, T. Scott and S. Hirsch, “Implications for Distribution Networks of High Penetration of Compact Fluorescent Lamps,” IEEE Trans. Power Delivery, 2009, Vol. 3, pp. 584–591.