

เอกสารอ้างอิง

1. K.J. Hong, J.M. Kim, H.S. Kim, Microstructure and properties of CaO-ZrO₂-SiO₂ glass-ceramics prepared by sintering, Journal of the European Ceramic Society, 23 (2003) 2193–2202
2. G. Bolelli, V. Cannillo, L. Lusvarghi, T. Manfredini, C. Siligardi, C. Bartuli, A. Loreto, T. Valente, Plasma-sprayed glass-ceramic coatings on ceramic tiles: microstructure, chemical resistance and mechanical properties, Journal of the European Ceramic Society, 25(11) 2005, 1835-1853
3. M. Piispanen a, J. Määttä b, S. Arevac, A.-M. Sjöberg b, M. Hupaa, L. Hupaa, Chemical resistance and cleaning properties of coated glazed surfaces, Journal of the European Ceramic Society 29 (2009) 1855–1860
4. V. Cannillo, L. Esposito, E. Rambaldi, A. Sola, A. Tucci, Microstructural and mechanical changes by chemical ageing of glazed ceramic surfaces, Journal of the European Ceramic Society 29 (2009) 1561–1569
5. C. Siligardi, P. Miselli, L. Lusvarghi, M. Reginelli, Influence of CaO-ZrO₂-Al₂O₃- SiO₂ glass-ceramic frits on the technological properties of porcelain stoneware bodies,Ceramic International,37(2011) 1851-1858
6. ASTM B 117 Practice for operating salt spray (Fog) apparatus



