

เอกสารอ้างอิง

- ณัฐธิดา หวังประดิษฐ์. 2553. อิทธิพลของชนิดและปริมาณของสารตัวเติมอนินทรีย์และปัจจัยการเตรียมต่อสมบัติของเทอร์โมพลาสติกวัลคาไนซ์ทนไฟจากการเบลนด์ยางธรรมชาติกับพอลิโพรพิลีน. วิทยานิพนธ์วิทยาศาสตรบัณฑิต สาขาเทคโนโลยียาง คณะวิทยาศาสตร์และเทคโนโลยี มหาวิทยาลัยสงขลานครินทร์.
- สุภัทรา ตั้งฤกษ์วาราสกุล. 2554. อิทธิพลของชั้นซิลิเกตต่อสมบัติการไหล สมบัติเชิงกล และความต้านทานต่อความร้อนของเทอร์โมพลาสติกวัลคาไนซ์จากการเบลนด์ยางธรรมชาติกับพอลิโพรพิลีน. วิทยานิพนธ์วิทยาศาสตรมหาบัณฑิต สาขาวิชาเทคโนโลยีพอลิเมอร์ บัณฑิตวิทยาลัย มหาวิทยาลัยสงขลานครินทร์.
- Abdou-Sabet, S., and Datta, S. 2000. Thermoplastic vulcanizates. In Polymer Blends. Paul, D. R. and Bucknall, C.B., editors. Wiley Interscience Publication, New York, pp. 517-555.
- Alexandere, M. and Dubois, P. 2000. Polymer-layered silicate nanocomposites : preparation, properties and uses of a new class material. Material Science and Engineering. 28, 1-63.
- American Society for Testing and Materials (ASTM). 2005. Standard test method for vulcanized rubber and thermoplastic elastomer- tension: D412-98a. In ASTM. AnnualBook Standard Testing Methods, Vol 09.01. Pennsylvania.
- American Society for Testing and Materials (ASTM). 2005. Standard test method for rubber property- deterioration in an air oven: D573-04. In ASTM. Annual Book Standard Testing Methods, Vol 09.01. Pennsylvania.
- American Society for Testing and Materials (ASTM). 2005. Standard test method for rubber property- durometer hardness: D2240-04. In ASTM. Annual Book Standard Testing Methods, Vol 09.01. Pennsylvania.
- American Society for Testing and Materials (ASTM). 2000. Standard test method for measuring the minimum oxygen concentration to support candle-like combustion of plastics (oxygen index): D2863-00. In ASTM. Annual Book Standard Testing Methods, Vol 08.01. Pennsylvania.

- American Society for Testing and Materials (ASTM). 2011. Standard test method for heat and visible smoke release rate for materials and products using an oxygen consumption calorimeter: E1354-11. In ASTM. Annual Book Standard Testing Methods, Vol 04.07. Pennsylvania.
- Bagheri, R., Liauw, C.M., and Allen, N.S. 2008. Factors effecting the performance of montmorillonite/magnesium hydroxide/poly(propylene) ternary composites, 1 flame retardation and thermal stability. *Macromolecular Materials and Engineering*. 293, 114-122.
- Beyer, G. 2001. Flame retardant properties of EVA-nanocomposites and improvements by combination of nanofillers with aluminium trihydrate. *Fire and Materials*. 25, 193-197.
- Canaud, C., Visconte, L. L. Y. and Reis Nunes, R. C. 2001. Mechanical and flammability properties of ATH-filled EPDM compositions. *Macromolecular Materials and Engineering*. 286, 377-381.
- Cárdenas, M.A., García-López, D., Gobernado-Mitre, I., Merino, J.C., Pastor, J.M., Martínez, J. D., Barbeta, J. and Calveras, D. 2008. Mechanical and fire retardant properties of EVA/clay/ATH nanocomposites- Effect of particle size and surface treatment of ATH filler. *Polymer Degradation and Stability*. 93, 2032-2037.
- Chen, M., Ao, N.J., Liao, Y.Y., Chen, Y. and Zhou, H.L. 2006. Thermooxidative degradation of natural rubber/clay composite. *Journal of Applied Polymer Science*. 100, 3809–3815.
- Coran, A. Y. and Patel, R. P. 1996. Chapter 7 Thermoplastic elastomers based on dynamically vulcanized elastomer/thermoplastic blends. In *Thermoplastic Elastomers*. Holden, G., editors. Hanser Publishers., Munich, pp. 144-179
- Cross, M.S., Cuasack, P. A. and Hornsby, P. R. 2003. Effects of tin additives on the flammability and smoke emission characteristics of halogen-free ethylene-vinyl acetate copolymer. *Polymer Degradation and Stability*. 79, 309–318.
- Duin, M.V. and Machado, A.V. 2005. EPDM-based thermoplastic vulcanisates: crosslinking chemistry and dynamic vulcanization along the extruder axis. *Polymer Degradation and Stability*. 90, 340-345.

- Duin, M. V. and Souphanthong, A. 1995. The chemistry of phenol-formaldehyde resin vulcanization of EPDM: Part I. Evidence for methylene crosslinks. *Rubber Chemistry and Technology*. 68, 717-727.
- Farzard, R. H., Hassan, A., Piah M. A. M. and Jawaid, M. 2013. Electrical and flammability properties of alumina trihydrate filled polypropylene/ethylene propylene diene monomer composites as insulators in cable Applications. *Polymer Engineering and Science*. 54, 493-498.
- Gabrielle, B., Lorthioir, C. and Lauprêtre, F. 2011. Thermal aging of interfacial polymer chains in ethylene-propylene-diene terpolymer/aluminum hydroxide composites: Solid-state NMR study. *The Journal of Physical Chemistry B*. 115, 12392–12400.
- Hanu, L.Z.G., Simon, G.P. and Cheng, Y.B. 2006. Thermal stability and flammability of silicone polymer composites. *Polymer Degradation and Stability*. 91, 1373-1379.
- Hao T., Bai, Z X, and Lu, L. X. 2013. Effect of magnesium hydroxide on the flame retardant properties of unsaturated polyester resin. *Procedia Engineering*. 52, 336 – 341.
- Haurie, L. Fernández, A. I., Velasco, J. I., Chimenos, M., Cuesta, J.-M. L. and Espiell, F. 2007. Thermal stability and flame retardancy of LDPE/EVA blends filled with synthetic hydromagnesite/aluminium hydroxide/montmorillonite and magnesium hydroxide/ aluminium hydroxide/montmorillonite mixtures. *Polymer Degradation and Stability*. 92, 1082-1087.
- Hippi, U., Mattila, J., Korhonen, M. and Seppälä, J. 2003. Compatibilization of polyethylene/aluminium hydroxide (PE/ATH) and polyethylene/magnesium hydroxide (PE/MH) composites with functionalized polyethylenes. *Polymer*. 44, 1193-1201.
- Hull, T. R., Witkowski, A. and Hollingbery, L. 2011. Fire retardant action of mineral fillers. *Polymer Degradation and Stability*. 96, 1462-1469
- l’Abee, R., Sablong, R., Goossens, H., Van Duin, M., Spoelstra, A., and Duchateau, R. 2010. Thermoplastic vulcanizates based on highly compatible blends of isotactic poly(propylene) and copolymers of atactic poly(propylene) and 5-ethylidene-2-norbornene. *Macromolecular Chemistry and Physics*. 211, 334-344.

- Jiao, C. M. and Chen, X. L. 2010. Synergistic flame retardant effect of cerium oxide in ethylene-vinyl acetate/aluminum hydroxide blends. *Journal of Applied Polymer Science*. 116, 1889-1893.
- Joseph, P and Ebdon, J. R. 2000. Phosphorus-based flame retardants. In *Fire Retardancy of Polymeric Materials*. Wilkie, C.A. and Morgan A.B., editors. CRC Press Taylor & Francis Group., New York, pp. 107-127
- Joseph, P., and Tretsiakova-Mcnally, S. 2011. Reactive modifications of some chain- and step-growth polymers with phosphorus containing compounds: effects on flame retardance—a review. *Polymers for Advanced Technologies*. 22, 395–406.
- Khanlari, S., and Kokabi, M. 2010. Thermal stability, aging properties and flame resistance of NR-based nanocomposite. *Journal of Applied Polymer Science*. 119, 855-862.
- Khunová, V. and Liauw, C.M. 1999. Advances in the reactive processing of polymer composites based on magnesium hydroxide. *Chemical Papers*. 54, 177-182.
- Kiliaris, P. and Papaspyrides, C.D. 2010. Polymer/layered silicate (clay) nanocomposites: An overview of flame retardancy. *Progress in Polymer Science*. 35, 902-958.
- Laoutid, F., Gaudon, P., Taulemesse, J.-M., Lopez Cuesta, J.-M., Velasco, J.I., and Piecaczyk, A. 2006. Study of hydromagnesite and magnesium hydroxide based fire retardant systems for ethylene-vinyl acetate containing organo-modified montmorillonite. *Polymer Degradation and Stability*. 91, 3074-3082.
- Loakijchareon, P. 2000. The phase morphology of blends of natural rubber with crystalline hydrocarbon plastics. Ph.D. Thesis, The University of Akron.
- Lopattananon, N., Tanglakwaraskul, S., Kaesaman, A., Seadan, M. and Sakai, T. 2013. Partially dynamically vulcanized thermoplastic elastomer based on natural rubber-polypropylene-clay nanocomposites. *Advanced Materials Research*. 747, 230-233.

- Lu, S-Y. and Hamerton, I. 2002. Recent developments in the chemistry of halogen-free flame retardant polymers. *Progress in Polymer Science*. 27, 1661-1712.
- Liu, Q., Zhang, Y., and Xu, H. 2008. Properties of vulcanized rubber nanocomposites filled with nanokaolin and precipitated silica. *Journal of Applied Polymer Science*. 42, 232-237.
- Liu, L., Jia, D., Luo, Y., Li, B. 2009. Structure and flammability properties of NR-organoclay nano composites. *Polymer Composites*. 30, 107-110.
- Morgan, A.B. and Gilman, J.W. 2013. An overview of flame retardancy of polymeric materials: application, technology and future directions. *Fire and Materials*. 37, 259-279.
- Nakason, C., Tobprakhon, A., and Kaesaman, A. 2005. Thermoplastic Vulcanizates Based on Poly(methyl methacrylate)/Epoxidized Natural Rubber Blends: Mechanical, Thermal, and Morphological Properties. *Journal of Applied Polymer Science*. 98, 1251-1261.
- Nakason. C., Nuansomsri, K., Kaesaman. A. and Kiatkamjornwong, S. 2006a. Dynamic vulcanization of natural rubber/high-density polyethylene blends: effect of compatibilization, blend ratio and curing system. *Polymer Testing*. 25, 782-796.
- Nakason, C., Saiwari, S. and Kaesaman, A. 2006b. Rheological properties of maleated natural rubber/polypropylene blends with phenolic modified polypropylene and polypropylene-g-maleic anhydride compatibilizers. *Polymer Testing*. 25, 413-423.
- Nakason, C., Wannavilai. P. and Kaesaman. A. 2006c. Thermoplastic vulcanized based on epoxidized natural rubber/polypropylene blends: effect of compatibilizers and reactive blending. *Journal of Applied Polymer Science*. 100, 4729-4740.
- Nakason. C., Jaminno. S, K., Kaesaman. A. and Kiatkamjornwong, S. 2008. Thermoplastic elastomer based on high-density polyethylene/natural rubber blends: rheological, thermal, and morphological properties. *Polymers for Advanced Technologies*. 19, 85-98.

- Peterson, J. D., Vyazovkin, S. and Wight, C. A. 2001. Kinetics of the Thermal and Thermo-Oxidative Degradation of Polystyrene, Polyethylene and Poly(propylene). *Macromolecular Chemistry and Physics*. 202, 775–784.
- Qin, H., Zhang, S., Zhao, C., Hu, G. and Yang, M. 2005. Flame retardant mechanism of polymer/clay nanocomposites based on polypropylene. *Polymer*. 46, 8386–8395.
- Radush, H. J. 2006. Phase Morphology of Dynamically Vulcanized Thermoplastic vulcanizates. In *Micro- and Nanostructured Multiphase Polymer Blend Systems Phase Morphology and Interfaces*, Harrats, C., Thomas, S. and Groeninckx, G., editors. CRC Press Taylor & Francis Group., New York, pp. 295-330.
- Ray, S. S., and Okamoto, M. 2003. Polymer/layered silicate nanocomposites : a review from preparation to processing. *Progress in Polymer Science*. 28, 1539-1641.
- Rothon, R.N. and Hornsby, P.R. 1996. Flame retardant effects of magnesium hydroxide. *Polymer Degradation and Stability*. 54, 383-385.
- Sain, M., Park, S.H., Suhara, F. and Law, S. 2004. Flame retardant and mechanical properties of natural fibre-PP composites containing magnesium hydroxide. *Polymer Degradation and Stability*. 83, 363-367.
- Saiwari, S. 2013. Post-consumer tires back into new tires : devulcanization and re-utilization of passenger car tires. Ph.D. Thesis, The University of Twente.
- Sener, A. A. and Demirhan, E. 2007. The investigation of using magnesium hydroxide as a flame retardant in the cable insulation material by cross-linked polyethylene. *Materials and Design*. 29, 1376–1379
- Sircar, A.K. 1991. Analysis of elastomer vulcanizate composition by TG-DTG Techniques. A Meeting of The Rubber Division, American Chemical Society, Toronto, Ontario, Canada, May 21-24, 1991, 6.
- Sombatsompop, N., Wimolmala, E. and Markpin, T. 2007. Fly-ash particles and precipitated silica as fillers in rubbers. II. effects of silica content and Si69-treatment in natural rubber/styrene-butadiene rubber vulcanizates. *Journal of Applied Polymer Science*. 104, 3396-3405.

- Thitithammawong, A., Nakason, C., Sahakaro, K., and Noordermeer, J. 2007. Effect of different types of peroxides on rheological, mechanical, and morphological properties of thermoplastic vulcanizates based on natural rubber/polypropylene blends. *Polymer Testing*. 26, 537-546.
- Touré, B., Lopez Cuesta, J.-M., Longerey, M., and Crespy, A. 1996. Incorporation of natural flame retardant fillers in an ethylene-propylene copolymer, in combination with halogen-antimony system. *Polymer Degradation and Stability*. 54, 345-352.
- Valadares, L.F., Leite, C.A.P. and Galembeck, F. 2006. Preparation of Natural Rubber-Montmorillonite Nanocomposite in aqueous Medium : Evidence for Polymer-Platelet Adhesion. *Polymer*. 47, 672-678
- Varghese, H., Bhagawan, S.S., SomeswaraRao, S. and Thomas, S. 1995. Morphology, mechanical and viscoelasticbehaviour of blends of nitrile rubber and ethylene-vinyl acetate copolymer. *European Polymer Journal*. 31, 957-967.
- Varghese, S., Alex, R. and Kuriakose, B. 2004. Natural rubber-Isotactic Polypropylene Thermoplastic Blends. *Journal of Applied Polymer Science*. 92, 2063-2068
- Wang, G.L., Jiang, P.-K., Zhu, Z.-K. and Yin, J. 2002. Morphology and properties of linear low-density polyethylene highly loaded with aluminium hydroxide. *Chinese Journal of Polymer Science*. 20, 253-259.
- Zeus Industrial Products. 2005. Flammability of Polymers. Available online: http://www.zeusinc.com/.../zeusinc/.../Zeus_Flammability.pdf [March 28, 2012]
- Zhang, J., Hereid, J., Hagen, M., Bakirtzis, D., Delichatsios, M.A., Fina, A., Castrovinci, A., Camino, G., Samyn, F. and Bourbigot, S. 2009. Effects of nanoclay and fire retardants on fire retardancy of a polymer blend of EVA and LDPE. *Fire Safety Journal*. 44, 504-513.
- Zilberman, J., Hull, T. R., Price, D., Milnes, G. J. and Keen, F. 2000. Flame Retardancy of Some Ethylene Vinyl Acetate Copolymer-Based Formulations. *Fire and Materials*. 24, 159-164.