

เอกสารอ้างอิง

- มนตรี พิรุณเกษตร.2553.กลศาสตร์ของไหล Fluid Mechanics. พิมพ์ครั้งที่ 6. กรุงเทพฯ: วิทยพัฒน์.
- ปราโมทย์ เฑชะอำไพ.2545.ระเบียบวิธีไฟไนต์เอลิเมนต์เพื่อการคำนวณพลศาสตร์ของไหล. พิมพ์ครั้งที่ 1.กรุงเทพฯ:สำนักพิมพ์แห่งจุฬาลงกรณ์มหาวิทยาลัย.
- ศูนย์ความเป็นเลิศด้านฟิสิกส์, 2010, “Microfluidics คือ อะไรและมีประโยชน์อย่างไร” [ระบบออนไลน์] http://www.thepecenter.org/src/qa_read.php?question_id=1, 22 ตุลาคม.
- Bosch Sensor Tech GmbH, 2005, www.bosch-sensortec.com, Ver.1.0112005 Germany.
- Bruss H., 2008. Theoretical Microfluidics. Oxford University Press, New York.
- Cao B.Y., Chen M., Guo Z. ,2006, “Effect of surface roughness on gas flow in microchannels by molecular dynamics simulation”, *Int. J. Eng. Sci.*,44,927-937.
- CapacitiveImaging.com, 2006, “Capacitive imaging” , [online] <http://www.capacitiveimaging.com/> ,10 Nov.
- Chen Y., Zhang C., Shi M., Peterson G. P.,2009, “Role of surface roughness characterized by fractal geometry on laminar flow in microchannels”, *Phys. Rev. E*,80,026301.
- Cheung K., Gawad S., Renaud P. , 2005, “Impedance spectroscopy flow cytometry: On-chip label-free cell differentiation” .*CytometryA*, vol.65 ,issue 2, 124-132.
- Dean W.R. and Hurst J.M., 1959, “Note on the motion of fluid in curved pipe”, University College,London,W.C.I.
- Eggers J.,1994, “Theory of drop formation”, *Phys.Fluids*, 7 (5), 941-953.
- Ernst A., Streule W., Schmitt N., Zengerle R. and Koltay P.,2009, “A capacitive sensor for non-contact nanoliter droplet detection”, *Sens. Actuators, A*.vol.25,issue 1,57-63.
- Fainerman V.B., Makievski A.V., Miller R.,2004, “Accurate analysis of the bubble formation process in maximum bubble pressure tensiometry”, *Rev. Sci. Instrum*,75(1),213-221.
- Fox R.W., Pritchard P. J., McDonald A. T., 2010, “Introduction to fluid mechanics”, 7th, John Wiley & Sons, New York.

- Fraden J., 2003. "Handbook Of Modern Sensor", 3rd ed, San Diego: Advanced Monitors Cooperation, 340-349.
- Gadelmawla E.S., Koura M.M., Maksound T.M.A., Elewa I.M., Soliman H.H., 2002, "Roughness parameters", *J. Mater. Process. Technol.*, issue 1, vol.123, 133-145.
- Gomez-Sjoberg R., Morissette D.T., Bashir R. "Impedance microbiology-on-a-chip: Microfluidic bioprocessor for rapid detection of bacterial metabolism", *IEEE/ASME*, vol.14, issue 4, 829-838.
- Greitzer E. M., Tan C. S. and Graf M. B., 2004, "Internal flow : concepts and applications". Cambridge, UK ; New York : Cambridge University Press.
- Guijt R, Baltussen M., Steen E. G., Frank, H. Billiet, Schalkhammer H., Laugere T., Vellekoop F., Berthold M., Sarro A., Van Dedem L., 2001, "Capillary electrophoresis with on-chip four-electrode capacitively", *Electrophoresis*, 22, 2537-2541.
- Günther A., Khan S. A., Thalmann M., Trachsel F. and Jensen K. F., 2004, "Transport and reaction in microscale segmented gas-liquid flow", *Lab Chip*, issue 4, 278-286.
- Garstecki P., Fuerstman M. J., Stone H. A., Whitesides G. M., 2006, "Formation of droplets and bubbles in a microfluidic T-junction-scaling and mechanism of break-up", *Lab Chip*, 6, 437-446.
- Halbo L. and Ohlckers P. , 1995. "Electronic Components, Packaging and Production", University of Oslo, Norway.
- Harada T., Suzuki Y., Koshizuka S., Arakawa T., Shoji S., 2006, "Simulation of droplet generation in micro flow using MPS method". *JSME Int J., Ser. B*, 49(3), 731-737.
- Hung L.H., Choi K. M., Tseng W.Y., Tan Y.C., Shea K. J. and Lee A. P. , 2006, "Alternating droplet generation and controlled dynamic droplet fusion in microfluidic device for CdS nanoparticle synthesis" *Lab Chip*, 6, 174-178
- Judy J., Maynes D., Webb B.W., 2002, "Characterization of frictional pressure drop for liquid flows through microchannels", *Int. J. Heat Mass Transfer*, 45, 3477-3489.
- Khan M.A.H., 2006, "Singularity behavior of flow in a curve pipe", *Int .J. of Applied Mechanics and Engineering*, vol.11, No.3, 699-704.

- Kim D., Chesler N.C., and Beebe D.J., 2006, "A method for dynamic system characterization using hydraulic series resistance," *Lab Chip*, vol.6, 325-334.
- Kulkarni A.S., 2004, "Effect of surface roughness in microchannel flow", Master's Thesis, Department of Mechanical and Aerospace Engineering, University of Florida.
- Klasner S.A., Price A.K., Hoeman K.W., Wilson R.S., Bell K.J. and Culbertson C.T., 2010, "Paper-based microfluidic devices for analysis of clinically relevant analytes present in urine and saliva", *Anal Bioanal Chem.* Jul;397(5):, Epub 2010 Apr 28, 1821-9.
- Kandlikar S. G., Schmitt D., Carrano A. L., Taylor J. B., 2005, "Characterization of surface roughness effects on pressure drop in single-phase flow in minichannels", *Physics of Fluids A*. Vol. 17, 100606.
- Kirshner J. M., 1966, *Fluid Amplifiers*, McGraw-Hill, New York. Kurtz A.D. and Gravel C.L., 1967, "Semiconductor transducers using transverse and shear piezoresistance", Proc. 22nd ISA Conference.
- Kontack Chemie, 2004, "Technical Information about the application of photoresist varnish POSITIV 20". CRC Industries, Belgium.
- Ligrani P. M., 1994, "A study of Dean vortex development and structure in a curved rectangular channel with aspect ratio of 40 at Dean number up to 430", *Contractor Report ARL-CR-144*, NASA. California.
- Linear Tech, 1994, "Micropower Sampling 12-Bit A/D Converters In S0-8 Packages", CA, USA.
- Mala Gh. M. and Li D., 1990, "Flow characteristics of water in microtubes", *Int. J. Heat Fluid Flow*, 20, 142-148.
- Melin J. and Quake S. R., 2007, "Microfluidic large-scale integration: "the evolution of design rules for biological automation", *Annu. Rev. Biophys. Biomol. Struct.* vol.36, 213-31
- Microchip Technology Inc, 2003, "PIC16F87XA Datasheet", www.microship.com/download/en/devicedoc/39582b.pdf.
- Nakata A., Tanaka S., Sugano K., 2008, "Electrical Equivalent Circuit Modeling of microfluidic system containing piezoelectric valves, micropump and viscoelastic PDMS microchannel", *12th International Conference on Miniaturized Systems for Chemistry and Life Sciences October 12-13*, San Diego, California, USA.

- Niu X., Zhang M., Peng S., Wen W., and Sheng P., 2007, “Real-time detection, control, and sorting of microfluidic droplets”. *Biomicrofluidics*, 1.044101-0441012.
- Noort D. V., Mccaskill J. S., 2004, “Flows in micro fluidic networks: From theory to experiment”, *Natural Computing*, 3, 395-410.
- Puttaraksa N., Unai ., Rhodes M. W. , Singkarat K., Whitlow H. J., Singkarat S., 011, “Fabrication of a negative PMMA master mold for soft-lithography by MeV ion beam lithography”, *Nucl. Instr. and Meth. B*, doi:[10.1016/j.nimb.2011.01.053](https://doi.org/10.1016/j.nimb.2011.01.053)
- Robert W. Fox, Alan T. McDonald, Philip J. Pritchard.(2010). “Introduction to Fluid Mechanics”. Hoboken, NJ : John Wiley & Sons.
- Rawool A. S., Mitra S. K., Kandlikar S. G., 2006, “Numerical simulation of flow through microchannels with designed roughness”, *Microfluid Nanofluid*, 2, 215-221.
- Rhodes M.W., 2010, UV-exposure, Chiang Mai, Thailand. Schönfeld F. and Rensink D., 2003, “Simulation of droplet generation by mixing nozzles”, *Cheml Eng & Tech.* (5)26, 585–591.
- Singkarat K., Puttaraksa N., Kamwanna T., Ginamoon W., Charoennukul R. and Rhodes M.W., 2009, “Simple programmable syringe pump fabrication and testing”, Poster IM P6, SPC2009, Phetchburi, Thailand.
- Sudasan A. P., 2003, “Fabrication of masters for microfluidic devices using conventional printed circuit technology”, Master’s Thesis, Department of Chemical Engineering, University of Texas A&M.
- Som S. K., Biswas G., 2008, “Introduction to fluid mechanics and fluid machines”, 2nd, Tata McGraw-Hill Publishing Company, New Delhi.
- Tanigawa H., Ishihara T., Hirata M., and Susuki K.M. ,1985, “Integrated silicon pressure sensor”, *IEEE Trans. Electron Dev*, 32nd (7), 1191-1195.
- Taniselass S., Retnasamy V., Poopalan P., 2011, “Microchannel miter bend effects on pressure equalization and vortex formation”, *Microsyst Technol*, vol.17, 469–475.
- Taylor J.B., Carrano A. L., Kandlikar S. G., 2006, “Characterization of the effect of surface roughness and texture on fluid flow—past, present, and future”, *Int. J. Therm. Sci.* 45, 962-968.

- Tufte, O.N., Chapman, P.W. and Long, D., 1962, "Silicon diffused-element piezoresistive diaphragm", *J. Appl. Phys.* 33, 3322-3327.
- Unai S., Puttaraksa N., Pinchaipat R., Singkarat K., Rhodes M.W., and Singkarat S., 2010, "Fabrication of microfluidic chip based on etched wiring board technique (EWBT)", IM_01, SPC2010, Kanchanaburi, Thailand.
- Vedel S., 2009, "Millisecond Dynamics in Microfluidics: Equivalent Circuit Theory and Experiment", Master's Thesis, Department of Micro-and Nanotechnology Technical, University of Denmark.
- Wadsin Din Pun academy, 2010, [online] http://www.wadsin.co.cc/ferric_chloride.html.
- Whitesides G.M., 2006, "The origins and the future of microfluidics", *Nature*, Vol. 442, 27 July, 368-377.
- White C.M., 1929, "Stream line flow through curved pipes". In: *Proc. Roy. Soc. London A* 123, 645-663.
- Wu J., Cao W., Wen W., Chang D.C. and Sheng P., 2009, "Polydimethylsiloxane microfluidic chip with integrated microheater and thermal sensor". *Biomicrofluidics*, issue 3, vol. 1, 12005.
- Xiong R. and Chung J.N., 2008, "Effects of miter bend on pressure drop and flow structure in micro-fluidic channels", *Int. J. Heat Mass Transfer*, vol 51, 2914-2924.
- Yamamoto K., Wub X., Nozakib K., Hayamizub Y., 2006, "Visualization of Taylor-Dean flow in a curved duct of square cross-section". *Fluid Dyn. Res.*, vol. 38, 1-18
- Yao S., Hertzog D. E., Zeng S., Mikkelsen J. C., Santiago J. G., 2003, "Porous glass electroosmotic pumps: design and experiments", *J. Colloid Interface Sci.*, 268, 143-153.
- Zhiming L. and Yulu L., 1997, "A calculation method for fully developed flow in curved rectangular tube", *J. Appl. Math. Mech.*, Vol. 18, No. 4, 315-318.