

เอกสารอ้างอิง

- กิติ ภัคดิวัฒน์กุล,จำลอง ครูอุตสาหะ. (2542). Visual Basic 6 ฉบับโปรแกรมเมอร์. กรุงเทพฯ ,
เคทีพี คอมพ์ แอนด์ คอนซัลท์.
- สมบูรณ์ สุวีระ. (2539). เศรษฐศาสตร์วิศวกรรมทรัพยากรน้ำ. กรุงเทพฯ , คณะวิศวกรรมศาสตร์
จุฬาลงกรณ์มหาวิทยาลัย.
- Akca,L., Kinaci,C. and Karpuzcu,M. (1993). "A Model for Optimum Design of Activated
Sludge Plants". *Water Research*, 27(9):1461-1468.
- Canada,J.R., Sullivan,W.G. and White,J.A. (1996). *Capital investment analysis for engineering
and management*, Prentice Hall, New Jersey.
- Chapman,D.T. (1983). "The Influence of Process Variables on Secondary Clarification". *Journal
of Water Pollution Control Federation.*, 55(12): 1425-1434.
- Chi-Chung Tang, Brill,E.D., Jr and Pfeffer,J.T. (1987). "Comprehensive Model of Activated
Sludge Wastewater Treatment System". *Journal of Environmental Engineering*,
113(5): 952-969.
- Craig,E.W.,Meredith,D.D. and Middleton,A.C. (1978). "Algorithm for Optimal Activated Sludge
Design". *Journal of the Environmental Engineering Division*, 104(6):1101-1117.
- Daiger,G.T. and Roper,R.E., Jr. (1985). "The Relationship between SVI and Activated Sludge
Settling Characteristics". *Journal of Water Pollution Control Federation*, 57:859-866.
- Fox,R.L. (1971). *Optimization Methods for engineering design*, Addison-Wesley Publishing
Company.
- Grady,C.P.L., Jr. (1977). "Simplified Optimization of Activated Sludge Process". *Journal of the
Environmental Engineering Division*, 103(3):413-429.
- Hamming,R.W. (1973). *Numerical Methods for Scientist and Engineer*, New York , McGraw-
Hill Book Co.
- Henze,M., Grady,C.P.L.Jr., Gujer,W., Marais,G.V.R. and Matsuo,T. (1987). *Activated
Sludge Model No.1 IAWPRC Science and Technology Report No.1*, London
England.

- Kalbskopf K.H. 1972. "Discussion of the Design Parameter for Secondary Sedimentation Tanks". *Water Research*, 6:429-431.
- Kuester, J.L. and Mize J.H. (1973). *Optimization Techniques with Fortran*, New York, McGraw-Hill Book Company.
- Orhon, D. and Artan, N. (1994). *Modelling of Activated Sludge Systems*, Lancaster, Technomic Publication.
- Orth, H.M. (1986). *Model-based Design of Water Distribution and Sewage Systems*, John Wiley & Sons.
- Patterson, W.L. and Banker, R.F. (1971). *Estimating Cost and Manpower Requirements for Conventional Wastewater Treatment Facilities*, Environmental Protection Agency Water Pollution Control Research Series, No. 17090 DAN, Washington D.C.
- Qasim, S.R. (1999). *Wastewater Treatment Plants Planning, Design and Operation*, CBS College Publishing, New York.
- Rao, S.S. (1978). *Optimization Theory and Practice and Application*, Wiley Eastern Limited, New Delhi.
- Riddel, M.D.R., Lee, J.S. and Wilson, T.E. (1983). "Method for Estimating the Capacity of an Activated Sludge Plant". *Journal of Water Pollution Control Federation*, 57(4):360-368.
- Tchobanoglous, G. and Burton, F.L. (1991). *Wastewater Engineering: Treatment, Disposal, Reuse*, 3rd ed., McGraw Hill Book Co., Singapore.
- Van Haandel, A.C., Ekama, G.A. and Marais, G.V.R. (1981). "The Activated Sludge Process-3: Single Sludge Denitrification". *Water Research*, 15:1135-1152.
- Vesilind, P.A. (1968). "Design of Prototype Thickeners from Batch Settling Test". *Water Sewage Works*, 15: 302-307.