

เอกสารอ้างอิง

- [1] McColm, I. J., *Dictionary of ceramic science and engineering*, 2nd , Plenum Press, 1994.
- [2] Haerlting, G.H., Ferroelectric ceramics history and technology, *J. Am. Ceram. Soc.*, 1999;84:797-818.
- [3] Fletcher, R., Force transduction materials for human-technology interfaces, *IBM Systems Journal.*, 1996;35:630-638.
- [4] Shah, S. and Ramachandra, R.M.S., Preparation and dielectric study of high-quality PLZT x/65/35 (x=6,7,8) ferroelectric ceramic, *Appl. Phys. A.*, 2000;71:65-69
- [5] <http://www.ubka.uni-karlsruhe.de/vw/f2k/6058/6058.pdf> (5/1/2002)
- [6] Fu, R. and Zhang, T.Y., Effects of an electric field on the fracture toughness of poled lead zirconate titanate ceramics, *J. Am. Ceram. Soc.*, 2000;83:1215-18.
- [7] Tajima, K., Hwang, H.J. and Sando, M., Electric-field-induced crack growth behavior in PZT/Al₂O₃ composites, *J. Am. Ceram. Soc.*, 2000;83:651-653.
- [8] Hwang, H.J., Yasuoka, M., Sando, M., Toriyama, M. and Niihara, K., Frabrication, sinterability, and mechanical properties of lead zirconate titanate/silver composites, *J. Am. Ceram. Soc.*, 1999;82:2417-2422.
- [9] Nijmeijer, A. and Kruidhof, H., Synthesis and properties of lead magnesium niobate zirconate relaxor materials, *J. Am. Ceram. Soc.*, 1997;80:2717-2721.
- [10] Derby, B., Hills D. and Ruiz C., *Material for engineering (a fundamental design approach)*, Longman scientific & technical, 1992.
- [11] Lee, W.E., Rainforth, W.M., *Ceramic microstructure control by processing*, Chapman & Hall, 1994.
- [12] Askeland, D.R., *The science and engineering of materials*, 2nd S.I. edition, Chapman & Hall, 1990.
- [13] Colliou, A.Mc. and Powney, D.J., *The meacharnical and thermal properties of materials*, Crane Russak & company, Inc., 1973.

- [14] Watchman, J.B., *Mechanical properties of ceramics*, John Wiley & Son, Inc., 1996.
- [15] Callister Jr., W.D., *Materials science and engineering an introduction*, 3rd, John Wiley & Son, Inc., 1994.
- [16] Meyers, M.A. and Chawla, K.K., *Mechanical behaviors of materials*, Prentice-hall international, Inc., 1999.
- [17] Marshall, D.B., Noma, T. and Evans, A.G., A simple method for determining elastic-modulus-to-hardness ratios using Knoop indentation measurement, *J. Am. Ceram. Soc.*, 1982;65:c-175-176 .
- [18] Sakamoto, S., Yoshinaka, M., Hirota, K. and Yamaguchi, O., Mechanical properties and electrical conductivity of Co_3O_4 ceramics, *J. Am. Ceram. Soc.*, 1997;80:267-268.
- [19] Kamlah, M., Review article ferroelectric and ferroelastic piezoceramics modeling of electromechanical hysteresis phenomena, *Continuum. Mech. Thermodyn.* 2001.
- [20] http://www.ecertec.com/Docs/ULTRAXCat_201.pdf (10/12/2001)
- [21] <http://www.mse.stanford.edu/people/faculty/feigelson/project/PMNT/PMNThome.html> (23/11/2001)
- [22] Bhalla, A.S., Guo, R. and Roy, R., The perovskite structure-a review of its role in ceramic science and technology, *Mat. Res. Innovat.*, 2000;4:3-26.
- [23] Uchino, K., High electromechanical coupling piezoelectrics: relaxor and normal ferroelectric solid solution, *Solid State Ionic.*, 1998;108:43-52.
- [24] Yamashita, Y. and Ichinose, N., Can relaxor piezoelectric materials outperform PZT? (review), *IEEE international symposium on application of ferroelectric materials*, 1996; 1: 71-77.
- [25] Cho, S.H. and Biggers, J.V., Characterization and sintering of lead zirconate titanate powders, *J. Am. Ceram. Soc.*, 1983;66:743-746.
- [26] Moulson, A.J., Herbert, J.M., *Electroceramics materials and Application*, Chapman&Hall, 1993.

- [27] Jin, B.M., Kim, J. and Kim, S.C., Effect of grain size on the electrical properties of $\text{PbZr}_{0.52}\text{Ti}_{0.48}\text{O}_3$ ceramics, *Appl. Phys. A.*, 1997;65:53-56.
- [28] Kingon, A.I. and Clark, J.B., Sintering of PZT ceramics: I, atmosphere control, *J. Am. Ceram. Soc.*, 1983;66(4):253-256.
- [29] Garg, A. and Agrawal, D.C., Effect of net PbO content on mechanical and electromechanical properties of lead zirconate titanate ceramics, *Material Science and Engineering.*, 1999;B56:46-50.
- [30] Calderon-Moreno, J.M., Guiu, F., Jimenez, B., Reece, M.J. and Sohn, K.S., Anisotropy in the indentation fracture piezoelectric titanate ceramics, *Ferroelectric*, 1999;28:111-128.
- [31] Karatamasti, T., Lynch C.S., Lucato, S., Lupascu, D. and Rodel, J., R-curves in lead zirconate titanate (PZT), *Proc. IEEE 12th Int'l Symp. Application of Ferroelectrics*, 2000;1:19-22
- [32] Kim, N., Jang, S.J., and Shrout, T.R., Relaxor based fine grain piezoelectric materials, *Proc. IEEE 7th Int'l Sym. Application of Ferroelectrics*, 1991:605-609.
- [33] Fielding Jr., J.T., Jang, S.J., Shrout, T.R., Thermal degradation of relaxor-based piezoelectric ceramics, *Proc. IEEE 7th Int'l Sym. Application of Ferroelectrics*, 1991 :459-462.
- [34] Tandon, R.P. and Phar, A., Influence of the processing parameters on dielectric properties of PMN relaxor ceramics, *Proc. IEEE 7th Int'l Symp. Application of Ferroelectrics*, 1991: 573-576.
- [35] Kelly, J., Ferrey, G. and Safari, A., A comparison of the properties of (1-x)PMN-xPT ceramic near the morphotropic phase boundary prepared by sol-gel and columbite precursor methods, *Proc. IEEE 10th Int'l Symp. Application of Ferroelectrics*, 1991:699-702.
- [36] Abbattista, F., Rolando, P. and Grassi, G.B., *Ann. Chim.(Rome)*, 1970;60:426-435.
- [37] Ananta, S. and Thomas, N.W., Fabrication of PMN and PFN ceramics by two-stage sintering technique, *J. Euro. Ceram. Soc.*, 1999;19:2917-2930.

- [38] Titov, A.A., Krokhin, V.A., Zhulanov, N.K. and Melnikov, D.L., Preparation of chemically active powders of niobium and titanium oxides and synthesis of dielectric ceramic materials, *J. Mate. Proc. Tech.*, 1995;55:249-253.
- [39] Costa, A.L., Galassi C., Fabbi, G., Roncari, E. and Capini, C., Pyrochlore phase and microstructure development in lead magnesium niobate materials, , *J. Euro. Ceram. Soc.*, 2001;35:1165-1170.
- [40] <http://www.cimss.vt.edu/downloads/ActReport.pdf> (5/1/2002)
- [41] Megherhi, M.H., Dayton, G.O., Shrout, T.R. and Mecholsky Jr, J.J., Indentation fracture of lead magnesium niobate-based multiplayer composite structures, *J. Mate. Res.*, 1990;5:515-523.
- [42] Zhao, J. and Zhang, Q.M., Effect of mechanical stress on the electromechanical performance of PZT and PMN-PT ceramics, *Proc. IEEE 10th Int'l Symp. Application of Ferroelectrics.*, 1996;2:971-974.
- [43] Zhao, J., Zhang, Q.M. and Mueller, V., Uniaxial stress dependence of electromechanical and dielectric properties of 0.9PMN-0.1PT electroceramics, *Proc. IEEE 11th Int'l Symp. Application of Ferroelectrics.*, 1998;1:361-364.
- [44] Jun S.G. and Kim, N.K., Dielectric properties of PFN-PMN relaxor system prepared by B-site precursor methode, *J. Mater. Sci.*, 2000;35:2093-2097.
- [45] Yoo, J-H., Lee, Y-W., Hwang, S-M., Yoon, H-S., Jeong H-S., Kim, J-S. and Yoo C-S., Piezoelectric properties of PNW-PMN-PZT ceramics for high power piezoelectric transformer, *Proc. IEEE 12th Int'l Symp. Application of Ferroelectrics.*, 2000;1: 495-498.
- [46] Murty, R.K., Murty, S.N., Mouli, K.C. and Bhanumathi, A., Domain orientation and piezoelectric properties of Ag doped PMN-PZT ceramics, *Proc. IEEE 8th Int'l Symp. Application of Ferroelectrics.*, 1992:144-147.

- [47] Brown, L.F., Huang, J., Fitzgerald, J.J., Burghardt, N.R. and Winker, J.C., Electrical properties and chemical characterization of PMN and 0.90PMN-0.1PT, *Proc. IEEE Ultrasonics Symposium*, 1999:1025-1029.
- [48] Sumi, K., Qui, H., Kamei, H., Mariya, S., Murai, M., Shomada, M., Nishiwaki, T., Takei, K., Miyashita, S. and Hashimoto, M., Thickness dependence of structural and ferroelectric properties of sol-gel $\text{Pb}(\text{Zr}_{0.56}\text{Ti}_{0.44})_{0.90}(\text{Mg}_{1/3}\text{Nb}_{2/3})_{0.1}\text{O}_3$ films, *Thin Solid films*, 1998;330: 183-189.
- [49] Huang, H. and Hing P., The relationship between the mechanical properties and microstructure of sintered PZT, *J. Mater. Proc. Tech.*, 1990;89-90:538-543.
- [50] Okazaki, K., Mechanical behavior of ferroelectric ceramics, *Ceramic Bulletin*, 1984;63 (9):1150-1152.
- [51] Chen, w., Lupascu, D.C., Rodel, J. and Lynch, C.S., Short crack R-curves in ferroelectric and electrostrictive PLZT, *J. Am. Ceram. Soc.*, 2001;84:593-597.
- [52] Ricote, J., Pardo, L. and Jimenez, B., Mechanical characterization of calcium-modified lead titanate ceramics by indentation methods, *J. Mater. Sci.*, 1994;29:3248-3254.
- [53] Polli, D.A., Lange, F.F. and Levi, G.C., Metastability of fluorite, pyrochlore, and perovskite structures in the $\text{PbO-ZrO}_2\text{-TiO}_2$ system, *J. Am. Ceram. Soc.*, 2000;83:873-881.
- [54] Tanaka, H., Tabata, H., Kawai, T., Yamazaki, Y., Oki, S. and Ghoda, S., Controlling factors on the synthesis of $\text{Pb}(\text{Zr}_x\text{Ti}_{1-x})\text{O}_3$ films, *Thin Solid Films.*, 1996;289:29-33.
- [55] Sreedhar, K. and Mitra, A., Formation and transformation of cubic lead niobate pyrochlore solid solution, *J. Am. Ceram. Soc.*, 1999;82:1070-1072.
- [56] Bazant, Z.P., Size effect on structural strength: a review, *Archive of Applied Mechanics.*, 1999;69:703-725.