

TABLE OF CONTENTS

	Page
TABLE OF CONTENTS	i
LIST OF TABLES	ii
LIST OF FIGURES	iii
LIST OF ABBREVIATIONS	iv
INTRODUCTION	1
OBJECTIVES	4
LITERATURE REVIEW	5
MATERIALS AND METHODS	12
Materials	12
Methods	12
RESULTS AND DISCUSSION	15
CONCLUSIONS	37
LITERATURE CITED	38
APPENDICES	39
Appendix A Regression Analysis	40
Appendix B Gage Repeatability and Reproducibility	45
Appendix C Machine Correlation Transfer Function	54

LIST OF TABLES

Table	Page	
1	2 ³ Factorial Design	8
2	Defect per million for each Sigma	10
3	Key Parameter Inputs list	15
4	SWOT analysis	20
5	Single factor experiment	22
6	ANOVA result	23
7	Comparison averages of treatment pairs	23
8	Qualified machine condition	25
9	Result of GR&R of Leg_ht parameter at Section 3 on measurement type D	25
10	Ursa01's summary input parameters	27
11	Ursa01's an assumption input of parameters	28
12	Ursa01's an assumption input of incoming head parameters	29
13	Ursa01's an assumption input of process parameters	30
14	Sensitivity for Regression coefficient	33
15	Sensitivity for Head installation effect	34
16	3 ^k Design for experiment	34
17	Percents variation contributions of Hp after put new process inputs	34
18	Percents variation contributions of Hp after put new process inputs	35
19	Percents variation contributions of Hp before put new process inputs	35
20	Percents variation contributions of Hp before put new process inputs	35
21	Summary result of simulation	36
Appendix Table		
C1	Mean of head position	55
C2	The result of experiment	55

LIST OF FIGURES

Figure		Page
1	Sigma roadmap for the head pitch parameter	2
2	Sigma roadmap for the spring force parameter	3
3	Flow process chart of Ursa01 and Ursa02	3
4	Steps in a simulation study	6
5	Basic Laser Micrometers	9
6	Assembly variation of Hp parameter	13
7	Assembly variation of Sp parameter	13
8	The system application design concept	14
9	Process assessment flow chart	16
10	Transfer function development	17
11	Surface plot of Hp parameter for head down	18
12	Actual by predicted plot of Hp parameter for head down	18
13	Location of sections 1 and 2 on leg of actuator	21
14	Leg pitch calculation	21
15	Measuring position on Ursa01	22
16	GR&R result from Minitab	24
17	Experiment flow chart	26
18	The result of Ursa02 simulation	36
Appendix Figure		
A1	Regression analysis of Hp for head down	41
A2	Regression analysis of Hp for head up	42
A3	Regression analysis of Sp for head down	43
A4	Regression analysis of Sp for head up	44
B1	GR&R of Tip height head 0	47
B2	GR&R of Tip height head 1	49
B3	GR&R of Tip height head 2	51
B4	GR&R of Tip height head 3	53
C1	Linear regression of Leg_Ht 0	56
C2	Linear regression of Leg_Ht 1	57
C3	Linear regression of Leg_Ht 2	58
C4	Linear regression of Leg_Ht 3	59
C5	Linear regression of Leg_P 0	60
C6	Linear regression of Leg_P 1	61
C7	Linear regression of Leg_P 2	62
C8	Linear regression of Leg_P 3	63

LIST OF ABBREVIATIONS

α	=	Type-I error
ANOVA	=	Analysis of variances
BRG_Ht	=	Bearing height (inch)
BRG_P	=	Bearing pitch (degree)
DES	=	Discrete-event system
DOEs	=	Design of experiments
DPPM	=	Defect parts per million
GR&R	=	Gage Repeatability and Reproducibility
Hp	=	Head pitch of finish products (degree)
Hp(incoming)	=	Head pitch of incoming parts (degree)
KPIs	=	Key performance indicators
KPOs	=	Key Parameter Outputs
Leg_Ht	=	Leg height that is measurement reading from final tester (inch)
Leg_Ht(type D)	=	Leg height that is measurement reading from final tester (inch)
Leg_P	=	Leg pitch that is measurement reading from final tester (degree)
Leg_P(type D)	=	Leg pitch that is measurement reading from final tester (degree)
Sp	=	Spring force of finish products (gram)
Sp(incoming)	=	Spring force of incoming parts (gram)
VBA	=	Visual Basic Application
VOC	=	Voice of the Customer