

TABLE OF CONTENTS

	Page
TABLE OF CONTENTS	i
LIST OF TABLES	ii
LIST OF FIGURES	iv
INTRODUCTION	1
OBJECTIVES	4
LITERATURE REVIEWS	5
Extrusion	5
n-3 Fatty Acids	10
Vitamin E	34
MATERIALS AND METHODS	39
Materials	39
Methods	41
RESULTS AND DISCUSSION	65
Consumer Survey Conducted in Thailand	65
Effects of Extrusion Conditions on EPA, DHA and Vitamin E	
Retentions, Processing Parameters, Physical and Sensory Properties	
of Extruded Fish Snacks Supplemented with n-3 Fatty Acids	74
Optimization of Extrusion Conditions of the Extruded Fish Snack	119
CONCLUSION	125
LITERATURE CITED	127
APPENDICES	146
Appendix A Consumer survey questionnaire	147
Appendix B Consent form	153
Appendix C Instruction for sensory test	155
Appendix D Evaluation form for the acceptance test	158
CURRICULUM VITAE	160

LIST OF TABLES

Table	Page
1 n-3 Fatty acid content of fish, shellfish and fish oil	15
2 Effects of n-3 fatty acids on factors involved with inflammation	30
3 Fish powder composition	40
4 Box-Behnken experimental design for extrusion of a fish powder, rice, fish oil formulation	44
5 Moisture, fat, EPA, DHA and tocopherols contents of the ingredients	46
6 Extrusion formulation	46
7 Calculated composition of raw material based on analysis of ingredients	48
8 Screw configuration	53
9 Extrusion parameters	53
10 Specific absorption coefficients ($E^{1\%}_{cm}$) and maximum wavelength (λ_{max}) for tocopherols in 96% (v/v) ethanol solutions	62
11 Demographic characteristics of the survey participants	66
12 Consumer responses to questions about snacks and purchasing decisions	68
13 Response to questions about foods containing fish and/or fish oil	72
14 Recorded values of processing parameters during extrusion	77
15 Coefficients of parameters in the regression models for product temperature at the die, pressure at the die, % motor torque, SME and mean residence time of extruded snack according to the independent variables of barrel temperature (X_1), screw speed (X_2) and feed moisture content (X_3)	78
16 Moisture and fat content of the extrudates	91
17 Effect of extrusion conditions on EPA and DHA	94
18 Tocopherols and tocotrienols in extrudates	95

LIST OF TABLES (continued)

Table		Page
19	Coefficients of parameters in the regression models for EPA, DHA and EPA+DHA and vitamin E in extruded snack according to the independent variables of barrel temperature (X_1), screw speed (X_2) and feed moisture content (X_3)	97
20	Product moisture, product density, expansion ratio and shear strength of the extrudates	103
21	Coefficients of parameter in the regression models for product moisture, product density, expansion ratio and shear strength of extruded fish snack according to the independent variables of temperature (X_1), screw speed (X_2) and moisture content (X_3)	104
22	Means of hedonic rating scores for sensory attributes and overall acceptability	111
23	Coefficients of parameters in the regression models for sensory properties; appearance, color, aroma, flavor, texture and overall acceptability of extruded snack according to the independent variables of barrel temperature (X_1), screw speed (X_2) and feed moisture content (X_3)	112
24	Extrusion conditions for model verification	122
25	Observed and predicted values of EPA, DHA, EPA+DHA and total tocopherols and tocotrienols	123
26	Observed and predicted values of product density, expansion ratio and overall acceptability	124

LIST OF FIGURES

Figure		Page
1	Single screw extruder	8
2	Twin-screw extruder	8
3	Schematic of extrusion processing illustrating the effects of process variables on product attributes	11
4	Biosynthesis of long-chain fatty acids	12
5	Biosynthesis of eicosanoids from n-6 fatty acids and formation of AA, EPA and DHA	25
6	Conversion of AA, EPA and DHA to prostagladins, thromboxanes, and leukotriene eicosanoids	26
7	Structure of tocopherols and tocotrienols	35
8	A side-view diagram for the modified screw configuration No. 6	51
9	(A) Correlation between feeder feed rate (rpm) and material output (kg)	52
	(B) Correlation between water flow meter setting (mL/min) and water delivered (g)	52
10	(A) Contour plots of screw speed and feed moisture to product temperature ($^{\circ}\text{C}$) at the barrel temperature of 135°C	79
	(B) Contour plots of screw speed and feed moisture to pressure at the die ($\text{Pa} \times 10^6$) at the barrel temperature of 135°C	79
11	(A) Contour plots of screw speed and feed moisture to % motor torque at the barrel temperature of 135°C	81
	(B) Contour plots of screw speed and feed moisture to SME (kJ/kg) at the barrel temperature of 135°C	81
12	(A) Contour plots of screw speed and feed moisture to t_m (s) at the barrel temperature of 125°C	85
	(B) Contour plots of screw speed and feed moisture to t_m (s) at the barrel temperature of 135°C	85

LIST OF FIGURES (continued)

Figure		Page
12	(C) Contour plots of screw speed and feed moisture to t_m (s) at the barrel temperature of 145°C	85
13	(A) Contour plots of screw speed and barrel temperature to t_m (s) at the feed moisture content of 19%	86
	(B) Contour plots of screw speed and barrel temperature to t_m (s) at the feed moisture content of 21%	86
	(C) Contour plots of screw speed and barrel temperature to t_m (s) at the feed moisture content of 23%	86
14	(A) E(t) plots of the residence time distribution at different temperatures (♦ 125°C, ■ 145°C)	87
	(B) F(t) plots of the residence time distribution at different temperatures (♦ 125°C, ■ 145°C)	87
15	(A) E(t) plots of the residence time distribution at different screw speeds (♦ 150 rpm, ■ 300 rpm)	88
	(B) F(t) plots of the residence time distribution at different screw speeds (♦ 150 rpm, ■ 300 rpm)	88
16	(A) E(t) plots of the residence time distribution at different feed moisture (♦ 19 g/100g, ■ 23 g/100g)	89
	(B) F(t) plots of the residence time distribution at different feed moisture (♦ 19 g/100g, ■ 23 g/100g)	89
17	(A) Contour plots of screw speed and feed moisture on EPA in extrudates (mg/100g) at the barrel temperature of 135°C	98
	(B) Contour plots of screw speed and feed moisture on DHA in extrudates (mg/100g) at the barrel temperature of 135°C	98
	(C) Contour plots of screw speed and feed moisture on EPA+DHA in extrudates (mg/100g) at the barrel temperature of 135°C	98

LIST OF FIGURES (continued)

Figure		Page
18	(A) Contour plots of barrel temperature and feed moisture on vitamin E in extrudates (mg/100g) at the screw speed of 225 rpm	99
	(B) Contour plots of screw speed and feed moisture on vitamin E in extrudates (mg/100g) at the barrel temperature of 135°C (B)	99
19	(A) Contour plots of screw speed and feed moisture on product moisture (g/100g db) of the extrudates at the barrel temperature of 135°C	106
	(B) Contour plots of screw speed and feed moisture on product density (g/cm ³) of the extrudates at the barrel temperature of 135°C	106
	(C) Contour plots of screw speed and feed moisture on expansion ratio of the extrudates at the barrel temperature of 135°C	106
20	Contour plots of screw speed and feed moisture on hardness (N) of the extrudates at the barrel temperature of 135°C	109
21	Contour plot of temperature and feed moisture on the appearance of the extrudate at the screw speed of 225 rpm	114
22	(A) Contour plots of screw speed and feed moisture on the color acceptability of extrudate at the barrel temperature of 135°C	115
	(B) Contour plots of screw speed and feed moisture on aroma acceptability of extrudate at the barrel temperature of 135°C	115
23	(A) Contour plots of screw speed and feed moisture on the flavor acceptability of extrudate at barrel temperature of 135°C	116
	(B) Contour plots of screw speed and feed moisture on texture acceptability of extrudate at the barrel temperature of 135°C	116
24	Contour plots of screw speed and feed moisture on the overall acceptability of the extrudate at the barrel temperature of 135°C	117

LIST OF FIGURES (continued)

Figure		Page
25	Optimum screw speeds and feed moistures for extruding fish snack at the barrel temperature of 135°C a function of screw speed and raw material moisture content	120