TABLE OF CONTENTS

TABLE OF CONTENTS	i	
LIST OF TABLES ii		
LIST OF FIGURES	vi	
INTRODUCTION	1	
General Introduction	1	
Statement of Problems	1	
Objective of Research	2	
Scope of Research	2	
LITERATURE REVIEW	3	
Landslides	3	
Factors Affecting Landslide	8	
	0	
1	15	
-	20	
	21	
Cut Slope	25	
1	27	
	28	
MATERIALS AND METHOD	34	
Materials	34	
Method		
	35	
	37	
	37	
Rock Mass Rating (RMR) and Slope Mass Rating (SMR)		
	37	
	39	
1	39	
	10	
-	11	
	12	
	12	
	53	
	52	
	73	
6	30	
•	33	
Processing Landslide Susceptibility and Hazard Map by		
	36	
	95	
Processing Landslide Susceptibility and Hazard Map by		
	98	
Collect Slope Condition Data from Field Investigation		

TABLE OF CONTENTS (Continued)

Failure Verification (RMR included)	107
Processing Cut Slope Failure and Hazard Map by	
	109
	114
Processing Cut Slope Failure Map and Hazard Map by	
	116
6	123
Processing Cut Slope Probability of Failure Map by Considering	
RMR Factor Included	126
Logistic Multiple Regression Analysis by SMR Factor Included	130
Processing Cut Slope Probability of Failure Map by Considering	
SMR Factor Included	133
CONCLUSIONS	137
RECOMMENDATION	140
	141
APPENDIX	146

LIST OF TABLES

Table

1	The landslide potential and the rang of probability	11
2	The detailed descriptions of different weighted factor values	12
3	The landslide potential and the rang of total score	13
4	The detailed descriptions of different weighted factor values	14
5	The landslide potential and the rang of total score	15
6	Rock mass rating	21
7	Adjustment rating for joints	23
8	Adjustment rating for methods of excavation of slopes	23
9	Tentative description of SMR classes	24
10	Discontinuity condition factor λ	24
11	Range of standard cut slope gradients for bedrock soil	26
12	Rainfall (mm.) in Muang Phuket	29
13	Relative humidity (%) in Muang Phuket	30
14	Mean temperature (°C) in Muang Phuket	30
15	Mean max. temperature (°C) in Muang Phuket	31
16	Mean min. temperature (°C) in Muang Phuket	31
17	Population density	32
18	Data collection for the analysis of landslide sensitive area	36
19	Plan area of 7 factors	42
20	Landslide potential classification of rock type	53
20 21	Potential landslide level of rock series in 6 provinces	55
-1	(by rock type)	54
22	Landslide potential classification of lineament zone	55
23	Landslide potential classification of slope	55
23	Landslide potential classification of elevation	55
25	Landslide potential classification of surface drainage zone	55
26	Landslide potential classification of land used	56
20 27	Landslide potential classification of soil characteristic	56
28	Soil group (Department of Land Development, 2001)	56
20 29	Landslide potential classification of rainfall intensity	59
30	Landslide potential classification of rainfall intensity	60
31	Landslide potential classification of engineering soil properties.	60
32	The numerical weight assignment to the parameters influencing	00
32	the landslide potential in Phuket	61
33	1	01
33	The landslide potential and the range of total score for all return periods of rainfall	62
24	Predicted landslide susceptibility area considering 7 related factors	65
34		05
35	Predicted landslide hazard area for 5 return periods of rainfall	70
26	considering 7 related factors	72
36	Comparison of landslide potential area and landslide hazard area	70
27	considering 7 related factors	73
37	Field investigation in 14 watersheds	80
38	Field investigation data for RMR rating	83

LIST OF TABLES (Continued)

Table Page 39 Average rock mass rating classified by rock type 83 40 The numerical weight assignment to the RMR factor influencing the landslide in Phuket. 86 Area of landslide classes considered by including 7 related 41 factors and RMR factor..... 89 42 Predicted landslide hazard area for 5 return periods of rainfall include related factors and RMR factor..... 94 43 Example of SMR estimation PK06..... 95 44 Average slope mass rating classified by rock type 95 The numerical weight assignment to the SMR factor 45 influencing the landslide in Phuket..... 98 Area of landslide classes considered by including 7 related 46 factors and SMR factor 101 47 Predicted landslide hazard area for 5 return periods of rainfall including 7 related factors and SMR factor 105 48 The landslide potential and the range of total score considering RMR factor for all return period of rainfall..... 109 49 Area of failure cut slope classes considered by including 7 related factors and RMR factor..... 111 Predicted failure cut slope hazard area for 5 return periods 50 of rainfall including 7 related factors and RMR factor..... 113 51 The landslide potential and the range of total score considering SMR factor for all rainfall return period..... 116 Area of failure cut slope classes considered by including 7 52 related factors and SMR factor 118 53 Predicted failure cut slope hazard area for 5 return periods of rainfall including 7 related factors and SMR factor..... 121 54 Variable means between failure and non-failure of cut slope...... 124 Result of linear regression analysis for cumulative rainfall 55 intensity 3 days (RMR factors included) 124 Results of enter logistic procedure..... 56 125 Result of linear regression analysis for cumulative rainfall 57 intensity 3 day 100 years return period (RMR factors included)... 125 Results of enter logistic procedure..... 58 126 59 Parameter means and distribution of predictive failure of cut slope (RMR included)..... 129 Variable means between failure and non-failure of cut slope...... 60 131 Result of linear regression analysis for cumulative rainfall 61 intensity 3 days (SMR factors included)..... 131 Results of enter logistic procedure..... 62 132 Result of linear regression analysis for cumulative rainfall 63 intensity 3 days 100 years return period (SMR factors included) 132 64 Results of enter logistic procedure..... 133

LIST OF TABLES (Continued)

Table		Page
65	Parameter means and distribution of predictive failure of cut slope (SMR included)	136
Appendix T	able	
1	Slope characteristics obtained from field investigation	147
2	Slope characteristics obtained from field investigation for evaluated RMR and SMR	154
3	Conclusion of result USCS, Atterberg's limits, sieve analysis, and direct shear test, Phuket	168
4	Consistency index of soil following rock type	169
5	Data failure slope condition for regression analysis	170
6	Data non-failure slope condition for regression analysis	171

v

LIST OF FIGURES

Figure

1	Landslide type	4
2		5
3	Slope height, H, vs slope height factor, x	5
4	Topographic map of Phuket province	3
5		5
6	Rock mass rating (RMR) descriptions for field survey sheet	
		8
7		0
8		4
9		-5
10		-6
11		7
12		8
13		.9
14		0
15		1
16		2
17		3
18	Landslide susceptibility map by weighting factor method	
		64
19		5
20		6
21		7
22	Landslide hazard map considering 20 years return period of	
		8
23	Landslide hazard map considering 50 years return period of	
		9
24	Landslide hazard map considering 100 years return period of	
		0
25	Landslide hazard map in Phuket using 1, 5, 20, 50 and 100 years	
		1
26	Predicted landslide hazard area for 5 return periods of rainfall	
		2
27	6	4
28		5
29		6
30		6
31		7
32		7
33		8
34		8
35		9
36		1

LIST OF FIGURES (Continued)

Figure

37	Field survey locations, cut slope condition
38	Graph relationships between cut slope failures and RMR rating.
39	Graph relationships between cut slope non failures and RMR rating
40	Normal distribution curve RMR value classified by slope condition
41	Cumulative frequency of RMR value classified by slope condition
42	Landslide potential classified by RMR value
43	Landslide susceptibility map by considering 7 related factors and RMR factor
44	Area of landslide classes considered by including 7 related factors and RMR factor
45	Comparison between the landslide susceptibility map by considering 7 related factors and considered by including 7 related factors and RMR factor
46	Comparison of landslide classes between considered by 7 related factors and considered by including 7 related factors and RMR factor
47	The landslide hazard map in Phuket shown by rainfall intensity return period of 1, 5, 20, 50 and 100 years respectively
48	(RMR factor included) The landslide hazard map in Phuket by rainfall intensity return period of 1, 5, 20, 50 and 100 years respectively
49	(RMR factor included) Predicted landslide hazard area for 5 return periods of rainfall including 7 related factors and RMR factor
50	Comparison between the landslide hazard map by considering 7 related factors and considered by including 7 related factors and RMR factor
51	Comparison of landslide hazard between considered by 7 related factors and considered by including 7 related factors and
52	RMR factor Graph relationships between cut slope failures and SMR rating
53	Graph relationships between cut slope non failures and SMR rating
54	Normal distribution curve SMR value classified by slope condition
55	Cumulative frequency of SMR value classified by slope condition
56	Landslide potential classified by SMR value
57	Landslide susceptibility map by considering 7 related factors and SMR factor

LIST OF FIGURES (Continued)

Figure

Page

58	Area of landslide classes considered by including 7 related
7 0	factors and SMR factor
59	Comparison between the landslide susceptibility map 102
60	Comparison of landslide classes
61	The landslide hazard map in Phuket shown by rainfall
	intensity return period of 1, 5, 20, 50 and 100 years respectively
	(SMR factor included) 103
62	The landslide hazard map in Phuket by rainfall intensity return
	period of 1, 5, 20,50 and 100 years respectively
	(SMR factor included) 104
63	Predicted landslide hazard area for 5 return periods of rainfall
	including 7 related factors and RMR factor
64	Comparison between the landslide hazard map 106
65	Comparison of landslide hazard
66	Graph relationships between failure of cut slope and RMR factor 107
67	Graph relationships between failure of cut slope and RMR factor 107
68	Normal distribution of total score (7 related factors and
	RMR factor) classified by slope condition 108
69	Cumulative frequency of total score (7 related factors and
	RMR factor) classified by slope condition
70	Cut slope failure potential classified by 7 related factors and
	RMR factor
71	Area of failure cut slope classes considered by including 7
	related factors and RMR factor
72	Area of failure cut slope classes considered by including 7
	related factors and RMR factor
73	The failure cut slope of hazard map in Phuket showing rainfall
10	intensity return period of 1, 5, 20, 50 and 100 years respectively
	(RMR factor included)
74	Predicted failure cut slope hazard area for 5 return periods of
<i>,</i> .	rainfall including 7 related factors and RMR factor
75	Graph relationships between cut slope failures and SMR factor 114
76	Graph relationships between cut slope non failures and
10	SMR factor
77	Normal distribution of total score (7 related factors and SMR
11	factor) classified by slope condition
78	Cumulative frequency of total score (7 related factors and
10	SMR factor) classified by slope condition
79	
17	Cut slope failure potential classified by 7 related factors and SMR factor
80	SMR factor116Area of failure cut slope classes considered by including 7
80	
	related factors and SMR factor 117

viii

LIST OF FIGURES (Continued)

Figure

Page

81	Area of failure cut slope classes considered by including 7 related factors and SMR factor	118
82	Comparing between the failure cut slope hazard map	119
83	Comparison of failure cut slope hazard classes	119
84	The failure cut slope of hazard map in Phuket showing rainfall	
	intensity return period of 1, 5, 20, 50 and 100 years respectively	
	(SMR factor Include)	120
85	Predicted failure cut slope hazard area for 5 return periods of	
	rainfall including 7 related factors and SMR factor	121
86	Comparison of landslide hazard	122
87	Probability of failure of sensitive area for cut slope for 1 year	
	rainfall return period (RMR factor included)	127
88	Probability of failure of sensitive area for cut slope for 100 years	
	rainfall return period (RMR factor included)	128
89	Probability of failure of sensitive area for cut slope for 1 year	
	rainfall return period (SMR factor included)	134
90	Probability of failure of sensitive area for cut slope for 100 years	
	rainfall return period (SMR factor included)	135
91	Recommendation of landslide sensitive area for cut slope by	
	weighting factor analysis	138
92	Recommendation of landslide sensitive areas for cut slope by	
	logistic regression analysis	139

Appendix Figure

1	Raingage station	162
2	Cumulative rainfall intensity 3 days contour return period	
	1 years	163
3	Cumulative rainfall intensity 3 days contour return period	
	5 years	164
4	Cumulative rainfall intensity 3 days contour return period	
	20 years	165
5	Cumulative rainfall intensity 3 days contour return period	
	50 years	166
6	Cumulative rainfall intensity 3 days contour return period	
	100 years	167