

# The Use of Geosynthetics in Major Metropolitan Landfills in Perth, WA – Two Case Studies

L. Du Preez<sup>1</sup>, R. Beaman<sup>2</sup> and I. Watkins<sup>3</sup>

<sup>1</sup>Golder Associates Pty Ltd, Perth, Australia

<sup>2</sup>Sita Environmental Solutions, Perth Australia

<sup>3</sup>Mindarie Regional Council, Perth Australia

E-mail: LDuPreez@golder.com.au

## 1. INTRODUCTION

According to the latest available data approximately 8 million tonnes of waste was generated in Western Australia during 2008/2009, the majority of which was generated in the Perth Metropolitan area. Of this total only 2.6 millions tonnes was recycled with the remainder still going to landfill. Even though recycling activities are on the increase, due mainly to an increase in the landfill levy, it is clear that there is still a great need for well designed and properly managed landfill sites within the Perth Metropolitan area. All of the major landfills in the metropolitan area utilise geosynthetic materials to some extent due to regulatory requirements or lack of suitable natural construction materials. The use of various geosynthetics at two metropolitan landfill sites, namely South Cardup Landfill and Tamala Park Landfill, are described in this article.

## 2. REGULATIONS

The Environmental Protection Act 1986 and Environmental Protection Policies set out the governmental policies and objectives for waste management in Western Australia (WA). In addition Best Practice documents are available to provide guidelines on how the environmental objectives can be achieved (DEC, 2005; EPA, 2010). Based on the draft position statement recently issued by the Department of Environment and Conservation (DEC) all new and existing landfills in WA have to be sited, designed, operated and rehabilitated in accordance with the Victoria Best Practice document (EPA, 2010).

In accordance with the Environmental Protection Act both South Cardup Landfill (SCL) and Tamala Park Landfill (TPL) are classified as Class II (DEC, 1996) putrescible landfills and therefore require a liner system that will limit seepage to no more than 1000 litre/hectare/day. An appropriate liner system to achieve this requirement would typically be a compacted clay liner.

## 2. SOUTH CARDUP LANDFILL

The South Cardup landfill is located approximately 42 km to the south of Perth off South West Highway in the Shire of Jarrahdale Serpentine. The site is owned and managed by West Australian Landfill Services (WALS) which is jointly owned by Sita Environmental Solutions and Hanson Australia. The site is zoned as rural and is licensed to accept Class II waste.

The natural topography is relatively steep as the landfill is located at the foothills of the Darling Range. Stage 1 of the landfill has been constructed on the hill slopes, whereas Stage 2 is located in an old quarry. Stage 3 is located in between Stage 1 and 2 and has a large volume of airspace relative to its footprint due to its inverted cone shape. During the development of the landfill, geosynthetic materials have been used in the liner systems for the individual cells, the most recent of which was Cells 7 and 8 (construction completed in 2008 and 2010 respectively). In addition a variety of geosynthetics have been used in the capping systems of the closed sections of the landfill.

Typically an acceptable liner system required for a Class II landfill would be a compacted clay liner. However during the

development of the last two stages (Stage 2 and 3) which commenced in 2004, WALS opted to install a higher specification liner system than what is required by installing a composite liner system in both Stage 2 (Cell 5 and 6) and Stage 3 (Cell 7 and 8).

The Stage 2 basal liner system consists of an underdrainage system, followed from the bottom up by a Geosynthetic Clay Liner (GCL), a 2 mm thick high density polyethylene (HDPE), a non-woven cushion geotextile with a mass exceeding 600 g/m<sup>2</sup>, and a 300 mm thick drainage aggregate layer covered by a separation geotextile.

The Stage 2 side slope liner consisted of a minimum 3 m wide (horizontal measurement) engineered fill liner in conjunction with a GCL, 2 mm thick HDPE and non-woven cushion geotextile layer with a mass exceeding 600 g/m<sup>2</sup>. Drainage aggregate was placed by WALS as part of the operations on an ongoing basis.

Stage 3 basal liner system is also a composite liner system similar to the Stage 2 liner. The liner system comprises, starting from the bottom, an engineered natural soil layer consisting of low permeability soil, a GCL and a 2.0 mm thick HDPE geomembrane liner. This is followed by a cushion geotextile with a mass of 1000 g/m<sup>2</sup> below a 300 mm thick leachate aggregate layer. The mass and strength properties of the cushion geotextile were governed by the thickness of the waste within Stage 3, which is located at the deepest section of the final landfill.



Figure 1 South Cardup Landfill, Stage 3 Cell 8 construction

The South Cardup landfill has an extensive groundwater monitoring network with monitoring wells both upstream and downstream of the site and to date no contamination originating from the landfill has been detected.

An extensive stability analysis was carried out for Stage 3 due to the relative steepness of the topography and the final height of the waste in this area. Based on the outcome of the stability analysis the decision was made to make use of a high strength GCL in combination with a double textured geomembrane, in critical areas.



Various geosynthetics have been used throughout both the landfills discussed above either because of it being cost effective, technically superior to natural materials or for ease of construction. In future the use of geosynthetics is expected to continue and possibly expand to include an even wider variety of materials.

## **5. REFERENCES**

- Department of Environment and Conservation (previously Department of Environment). (1996) Landfill Waste Classification and Waste Definitions (As amended)
- Department of Environment and Conservation, Western Australia.(November 2005) Draft Siting, Design, Operation and Rehabilitation of Landfills
- Environmental Protection Authority, Victoria. (October 2010) Siting, Design, Operation and Rehabilitation of Landfills