

หนังสืออ้างอิง

- [1] www.thaipr.net
- [2] Schubert, E., Klassen, M., Zerner, I., Walz, C., Sepold, G. Light-weight structures produced by laser beam joining for future applications in automobile and aerospace industry. *Journal of Materials Processing Technology*. 2001; 115: 2-8.
- [3] Mathieu, A., Pontevecchi, S., Viala, J., Cicala, E., Mattei, S., Grevey, D. Laser brazing of a steel/aluminium assembly with hot filler wire (88% Al, 12% Si). *Materials Science & Engineering A*. 2006; 435-436: 19-28.
- [4] Mathieu, A., Shabadi, R., Deschamps, A., Suery, M., Mattei, S., Grevey, D., Cicala, E., Dissimilar material joining using laser (aluminum to steel using zinc-based filler wire). *Optics & Laser Technology*. 2007; 39: 652-661.
- [5] Murakami, T., Nakata, K., Tong, H., Ushio, M., Dissimilar metal joining of aluminum to steel by MIG arc brazing using flux cored wire. *ISIJ International*. 2003; 43: 1596-1602.
- [6] Zhang, H.T., Feng, J.C., He P., Hackl, H., Interfacial microstructure and mechanical properties of aluminum-zinc-coated steel joints made by a modified metal inert gas welding-brazing process. *Materials Characterization*. 2007; 58: 588-592.
- [7] Oikawa, H., Saito, T., Yoshimura, T., Nagase, T., Kiriyaama, T., Spot welding of aluminum clad steel to steel or aluminum--Dissimilar metal joining of steel to aluminum with intermediate layer. *Quarterly Journal of the Japan Welding Society*. 1996; 14: 69-80.
- [8] Kikuchi, M., Takeda, H., Morozumi, S., Bonding interfaces in friction and explosive welded aluminum and steel joints. *Journal of Japan Institute of Light Metals*. 1984; 34: 165-173.
- [9] Iordachescu, D., Quintino, L., Miranda, R., Pimenta, G., Influence of shielding gases and parameters on metal transfer and bead shape in MIG brazed joints of the thin zinc coated steel plates. *Materials & Design*. 2006; 27: 381-390.
- [10] Yu, Z., Li, R., Qi, K., Growth behavior of interfacial compounds in galvanized steel joints with CuSi_3 filler under arc brazing. *Transactions of Nonferrous Metals Society of China*. 2006; 16: 1391-1396.
- [11] Chew, K.H., Pang, J.H.L. Impact of drop-in lead free solders on microelectronics packaging. *Electronics Packaging Technology Conference*. 2005; 451-454.
- [12] Amagai, M., Toyoda, Y., Ohnishi, T., Akita, S. High drop test reliability: Lead-free solders. *Electronic Components and Technology Conference*. 2004; 1304-1309.
- [13] Yu, D.Q., Wu, C.M.L., Law, C.M.T., Wang, L., Lai, J.K.L. Intermetallic compounds growth between Sn-3.5Ag lead-free solder and Cu substrate by dipping method. *Journal of Alloys and Compounds*. 2005; 392: 192-199.

[14] Ma, X., Qian, Y., Yoshida, F. Effect of La on the Cu-Sn intermetallic compound (IMC) growth and solder joint reliability. Journal of Alloys and Compounds. 2002; 334: 224-227.



