

THESIS APPROVAL GRADUATE SCHOOL, KASETSART UNIVERSITY

Master of Engineering (Chemical Engineering)

DEGREE

Chemical Engineering		Chemical Engineering	
FIELD		DEF	PARTMENT
TITLE:	Investigation on Structural and Energ Surface of PEM Fuel Cell by Quan		
NAME:	Mr. Vasavis Punnasukhirom		
THIS THESIS HAS BEEN ACCEPTED BY			
	40		THESIS ADVISOR
(Associate Professor Thongchai Srinophakun, Ph.D.			
***	Lena Chypana		COMMITTEE MEMBER
(Miss Nanthiya Hansupalak, P	h.D.)
	Supa Hamangbur	_ ,	_COMMITTEE MEMBER
(Associate Professor Supa Hannongbu)
	CHM		DEPARTMENT HEAD
(_Ass	sistant Professor Thumrongrat Mung	charoen, Ph.D.)
APPROV	ED BY THE GRADUATE SCHOOL ON	31 May	2006
150 4 300 7 3	Sinni A	HhyL	DEAN
Associate Professor Vinai Artkongharn, M. A.			

Vasavis Punnasukhirom 2006: Investigation on Structural and Energetic Properties of Chitosan Membrane Surface of PEM Fuel Cell by Quantum Chemical Calculations.

Master of Engineering (Chemical Engineering), Major Field: Chemical Engineering,
Department of Chemical Engineering. Thesis Advisor: Associate Professor Thongchai Srinophakun, Ph.D. 68 pages.

ISBN 974-9846-33-8

One of the factors influenced the performance of Proton Exchange Membrane Fuel Cell (PEMFC) is the ability of proton transfer in the membrane. The cell membrane can be made from biopolymer such as chitosan. In this study, the proton transfer in water environment mechanism throughout the chitosan membrane was investigated to enhance the performance of the cell. Molecular Modeling technique was used to determine the geometrical parameters of chitosan oligomers by semiempirical PM3, AM1, ab initio HF/3-21G* and HF/6-31G* based on Gaussian software. The results show that the geometrical parameters of chitosan oligomers, bond lengths; and bond angles are in the same range. In addition, the results were also compared with the parameters from X-ray crystallographical data with a good agreement. The electronic property of conducting polymer can be calculated by HOMO-LUMO method. In this study, the energy gap of chitosan polymer obtained from PM3 is 0.42 eV and 0.89 eV from HF/6-31G*. From these results, the chitosan polymer can be applied as the conducting polymer because of its near zero energy gap. The proton transfer by hopping mechanism was investigated with 3 water contents; 10, 35, and 90%. The optimum water content was found at 30% with the chitosan pentamer of 20 active sites. The number of electron from this oligomer is 20 and the electrical current is 3.2×10^{-4} mA.

instractorial chocos

Student's signature

19

Thesis Advisor's signature

30,05,2006